

1 Connecting Perebor Conjectures: Towards a 2 Search to Decision Reduction for Minimizing 3 Formulas

4 **Rahul Ilango**

5 Massachusetts Institute of Technology, USA

6 rilango@mit.edu

7 — Abstract —

8 A longstanding open question is whether the search and decision formulations of the Minimum
9 Circuit Size Problem are equivalent. While it is widely conjectured that computing either version
10 requires “perebor,” or brute-force search, researchers have not yet ruled out the possibility that the
11 search problem requires exponential time but the decision problem has a linear time algorithm.

12 In this paper, we make progress in connecting the search and decision complexity of minimizing
13 formulas. Let MFSP denote the problem that takes as input the truth table of a Boolean function
14 f and an integer size parameter s and decides whether there is a formula for f of size at most s .
15 Let Search-MFSP denote the corresponding search problem where one has to output some optimal
16 formula for computing f .

17 Our main result is that given an oracle to MFSP, one can solve Search-MFSP in time polynomial
18 in the length N of the truth table of f and the number t of “near-optimal” formulas for f , in
19 particular $O(N^6 t^2)$ -time. While the quantity t is not well understood, we use this result (and some
20 extensions) to prove that given an oracle to MFSP:

21 ■ there is a deterministic $2^{O(\frac{N}{\log \log N})}$ -time oracle algorithm for solving Search-MFSP on all but a
22 $o(1)$ -fraction of instances, and

23 ■ there is a randomized $O(2^{.67N})$ -time oracle algorithm for solving Search-MFSP on *all* instances.

24 Intriguingly, the main idea behind our algorithms is in some sense a “reverse application” of the
25 gate elimination technique.

26 **2012 ACM Subject Classification** Theory of computation → Circuit complexity; Theory of compu-
27 tation → Problems, reductions and completeness

28 **Keywords and phrases** minimum circuit size problem, minimum formula size problem, gate elimina-
29 tion, search to decision reduction, self-reducibility

30 **Digital Object Identifier** 10.4230/LIPIcs.CCC.2020.31

31 **Funding** During this work the author was supported by an Akamai Presidential fellowship.

32 **Acknowledgements** I want to thank Eric Allender, Lijie Chen, Mathew Katzman, Aditya Potukuchi,
33 Michael Saks, Rahul Santhanam, Ryan Williams, and Lyu Xin for many helpful discussions regarding
34 this work. I would also like to thank the anonymous CCC reviewers and Dimitrios Myrisiotis for
35 helping improve the exposition in this work.

36 **1** Introduction

37 In his fascinating historical account, Trakhtenbrot [20] describes the early developments of
38 the Russian cybernetics program. Beginning in the 1950s, this program was largely driven by
39 a desire to understand the necessity of “perebor,” or brute-force, in solving various problems
40 related to complexity minimization. What Trakhtenbrot calls “Task 1” in [20] is an analogue¹
41 of what is now commonly referred to as the Minimum Circuit Size Problem, MCSP. In his

¹ We say analogue since Task 1 was defined in the slightly different model of switching circuits.



42 article, Trakhtenbrot delineates two versions of “Task 1”: an “existential version,” where
 43 given a Boolean function f one must compute the minimum number of gates needed in a
 44 circuit computing f , corresponding to MCSP and a “constructive version,” where one must
 45 produce such an optimal circuit for f , corresponding to Search-MCSP.

46 Both versions were conjectured to require “perebor,” or brute-force to solve. However,
 47 while it is clear that if perebor is required for MCSP then perebor must also be required for
 48 Search-MCSP, it is a longstanding open question (since at least 1999 [10]) to prove a reverse
 49 implication: that is, to show that if Search-MCSP requires brute-force to solve, then MCSP
 50 requires brute-force.

51 Indeed, this question is closely related to another major open question surrounding
 52 MCSP: is MCSP NP-complete? Despite being an open problem since the discovery of NP-
 53 completeness² in the 1970s and numerous fascinating papers studying MCSP, we still know
 54 little about the computational complexity of MCSP. The problem is known to lie in NP, but
 55 even formal evidence supporting or opposing the NP-completeness of MCSP is lacking. This
 56 is in contrast to other prominent problems that are believed to be intractable yet are not
 57 known to be NP-complete (such as integer factorization or the discrete logarithm³).

58 However, a remarkable line of research demonstrates that a proof that MCSP is NP-
 59 complete would have significant ramifications. For example, Murray and Williams [14] show
 60 that it would imply the breakthrough complexity separation $\text{EXP} \neq \text{ZPP}$, and Hirahara [8]
 61 shows that it implies a worst-case to average case reduction for NP (if the hardness holds for
 62 an approximate version of MCSP).

63 Kabanets and Cai observed that an NP-completeness proof for MCSP would also resolve
 64 the “search versus decision” question mentioned at the beginning of this paper. In particular,
 65 since SAT is known to have a polynomial-time search to decision reduction, MCSP being
 66 NP-complete would imply that MCSP would also have a polynomial-time search to decision
 67 reduction. Hence, the time complexity of computing MCSP and Search-MCSP would be
 68 equivalent up to a polynomial.

69 Because of this, finding a search to decision reduction for MCSP is, in fact, a *necessary*
 70 step to showing that MCSP is NP-complete, and Kabanets and Cai left finding such a
 71 reduction as an open question. Indeed, it is a bit unnerving (at least to the author) that
 72 researchers have not yet ruled out the possibility that MCSP has a linear-time algorithm
 73 but solving Search-MCSP requires exponential-time! The present work was born out of a
 74 motivation to (at least partially) mediate this large gap.

75 Alas, while we fail to improve the status of this question for MCSP, we make consider-
 76 able progress in connecting the search and decision complexity of the analogous *Formula*
 77 *Minimization Problem*, MFSP.

78 1.1 Prior Work

79 In light of the numerous research papers studying MCSP and its variants, we do not attempt
 80 to survey the full body of literature but rather concentrate on those works related to search
 81 to decision reductions and MFSP. We point a reader interested in a more detailed overview
 82 to Allender’s excellent new survey [1] and the references therein.

² [4] cites a personal communication from Levin that he delayed publishing his initial NP-completeness results in hopes of showing MCSP is NP-complete.

³ Intriguingly, it is known [18, 2] that both of these problems reduce to MCSP under randomized reductions!

83 **Search to decision reductions for MCSP.** There are two main prior works for search to
 84 decision reductions for MCSP-like problems. Both provide algorithms that find approximately
 85 optimal circuits that are efficient as long as MCSP has efficient algorithms. Interestingly,
 86 both algorithms require that MCSP actually has efficient algorithms and seemingly fail if they
 87 are “only” provided oracle access to MCSP (the reason is that the approximately optimal
 88 circuit that these algorithms output actually include a small MCSP circuit within them).

89 The first prior work is a celebrated paper by Carmosino, Impagliazzo, Kabanets, and
 90 Kolokolova [6] that establishes connections between algorithms for MCSP-like problems and
 91 PAC-learning of circuits. In their paper, they show the following theorem.

92 ► **Theorem 1** (Carmosino, Impagliazzo, Kabanets, and Kolokolova [6]). *Suppose $\text{MCSP} \in \text{BPP}$.
 93 Then there is a randomized polynomial-time algorithm that, given the truth table of a function
 94 f with n -bit inputs, outputs a circuit C of size at most $\text{poly}(s)$ such that $C(x) = f(x)$ for all
 95 but a $\frac{1}{\text{poly}(n)}$ fraction of inputs x , where s is the minimum size of any circuit computing f .*

96 Building on [6], Hirahara [8] proved a breakthrough worst-case to average-case reduction
 97 for an approximation version of MCSP. In said paper, Hirahara shows the following theorem.

98
 99 ► **Theorem 2** (Hirahara [8]). *Suppose for some $\epsilon > 0$ that one can approximate MCSP to
 100 within a factor of $N^{1-\epsilon}$ in randomized polynomial-time (where N is the length of the truth
 101 table). Then there is some $\epsilon' > 0$ such that, given a length- N truth table for computing f ,
 102 one can, in randomized polynomial-time, output a circuit for computing f (exactly) whose
 103 size is within a $N^{1-\epsilon'}$ factor of being optimal.*

104 Using similar ideas, Santhanam [19] independently obtained a comparable search-to-
 105 decision reduction (with somewhat better parameters than Theorem 2) for AveMCSP, a
 106 natural variant of MCSP where one asks for the smallest circuit computing a function on a
 107 0.9-fraction of the inputs.

108 We find it interesting that “approximate” search to decision reductions for MCSP have
 109 been a building block in these celebrated results. It seems to suggest that further exploring
 110 the interplay between the search and decision versions of MCSP could be a fruitful direction.

111 **Hardness of MFSP.** As with MCSP, we have good reason to believe that MFSP is intractable,
 112 since it is in some sense “hard” for cryptography computable in NC^1 .

113 ► **Theorem 3** (Razborov and Rudich [17], Kabanets and Cai [10]). *If $\text{MFSP} \in \text{P}$, then there
 114 are no pseudorandom function generators computable in NC^1 .*

115 Allender, Koucký, Ronneburger, and Roy [4] build on this connection to show that MFSP is
 116 hard to approximate if factoring Blum integers is intractable.

117 Despite the strength of this cryptographic hardness connection, we know very little about
 118 the complexity of MFSP unconditionally. Indeed, part of the difficulty is that it seems
 119 difficult to design reductions that make use of an MFSP (or MCSP) oracle, since we do not
 120 understand the model of formulas (or circuits) very well. Until very recently [7], it was even
 121 open whether MFSP was in $\text{AC}^0[2]$!

122 One reason for focusing on MFSP is that one might expect it to be an easier problem to
 123 analyze than MCSP since formulas are somewhat better understood than circuits. In support
 124 of this intuition, we know that the formula minimization problem for DNFs and $\text{DNF} \circ \text{XOR}$
 125 formulas are NP-complete [13, 9] and that the natural Σ_2 variant of MFSP is complete for
 126 Σ_2 [5].

127 However, counter to this intuition, there are some cases in which it has been more difficult
 128 to prove hardness for MFSP than for MCSP. While it is known that MCSP is hard for SZK
 129 under randomized reductions [3], it remains open to prove such a result for MFSP. We take
 130 this as further evidence of the subtleties involved in designing reductions for MFSP.

131 1.2 Our Results

132 In contrast to prior results, we examine the case of having to *exactly* solve Search-MFSP,
 133 that is, producing an exactly optimal (instead of approximately optimal) formula.

134 We define MFSP over the model of DeMorgan formulas (formulas with AND and OR
 135 gates) where the size of a formula is the number of leaf nodes in its binary tree. Our main
 136 results are robust to changes in the model however. In particular, unless otherwise stated,
 137 all our results also extend to the case when gates are from the full binary basis \mathbb{B}_2 and to
 138 the case when the notion of size is the number of wires or the number of gates.

139 Our main result is to show that one can efficiently find an optimal formula for a given
 140 function f using an oracle to MFSP when f has a small number of “near-optimal formulas”
 141 (we say what this means after our theorem statement).

142 ► **Theorem 4** (also Theorem 34). *There is a deterministic algorithm solving Search-MFSP*
 143 *using an oracle to MFSP that given a length- N truth table of a function f runs in time*
 144 *$O(N^6 t^2)$ where t is the number of “near-optimal” formulas computing f .*

145 **Defining “near-optimal” formulas.** We now define what we mean by “near-optimal” for-
 146 mulas. Let $L(f)$ denote the minimum size of any formula computing f . We say a formula φ
 147 is a *near-optimal formula* for $f : \{0, 1\}^n \rightarrow \{0, 1\}$ if φ has size at most $L(f) + n + 1$.

148 Furthermore, in counting the number of near-optimal formulas, we consider formulas that
 149 are isomorphic as labelled binary trees to be the same formula. This avoids counting many
 150 trivially equivalent formulas as distinct near-optimal formulas. See Section 2.2 for a precise
 151 definition.

152 **Bounding the number of near-optimal formulas.** Unfortunately, we do not understand
 153 the quantity t in Theorem 4 very well. However, using the nearly tight upper bounds by
 154 Lozhkin [11] on the maximum formula size required to compute an n -input function, we get
 155 that with high probability a uniformly random function on n -inputs has at most

$$156 \quad 2^{O\left(\frac{N}{\log \log N}\right)}$$

157 many near-optimal formulas where $N = 2^n$.

158 Thus, we have the following corollary.

159 ► **Corollary 5** (also Corollary 35). *There is an algorithm A for solving Search-MFSP on all*
 160 *but a $o(1)$ fraction of instances that runs in time $2^{O\left(\frac{N}{\log \log N}\right)}$ using an oracle to MFSP.*

161 Corollary 5 has a nice interpretation with respect to the porebor conjecture. The queries
 162 algorithm A (run on a truth table input of length N) makes to its MFSP-oracle can be
 163 answered using a deterministic brute-force algorithm in time $2^{(1+o(1))N}$. In particular, the
 164 queries A makes are of length at most $2N$ and have complexity at most $(1 + o(1)) \frac{N}{\log \log N}$.
 165 On the other hand, the naive brute-force algorithm for Search-MFSP on an input of length
 166 N runs in time $2^{(1+o(1))N}$. Thus, we have the following further corollary.

167 ► **Corollary 6** (Informal). *If the brute-force algorithm for Search-MFSP is essentially optimal*
 168 *on average, then the brute-force algorithm for MFSP is essentially optimal in the worst-case*
 169 *on a large subset of instances (in particular queries of length $2N$ with complexity at most*
 170 $(1 + o(1))\frac{N}{\log \log N}$).

171 It would be nice to improve the running-time of the algorithm in Corollary 5. The bound
 172 that $t \leq 2^{O(\frac{N}{\log \log N})}$ for a random function hardly seems tight. In fact, in the setting of
 173 Kolmogorov complexity, one can prove that a random string of length N has only $\text{poly}(N)$
 174 many near-optimal descriptions with high probability (this is because the upper bound on
 175 the maximum Kolmogorov complexity of a length- N string is much tighter than the one for
 176 formulas). If we could prove an analogous result for formulas, then Corollary 5 would give a
 177 polynomial-time search to decision reduction for a random function!

178 **Solving Search-MFSP in the worst-case.** We also give a reduction that shows that even in
 179 the worst-case, one can get exponential savings over the brute-force algorithm for Search-MFSP
 180 by using a MFSP-oracle. In light of Theorem 4, a natural approach is to split into two cases:

- 181 ■ If there are a lot of near-optimal formulas for f , then just guess random formulas and see
 182 if they compute f .
- 183 ■ If there are not a lot of near-optimal formulas for f , then run the algorithm in Theorem 4.

184 However, this approach will only be able to output a near-optimal formula for computing
 185 f , and we desire to solve Search-MFSP exactly.

186 We manage to overcome this issue and prove the following theorem.

187 ► **Theorem 7** (also Theorem 42). *There is a randomized algorithm for solving Search-MFSP*
 188 *using an oracle to MFSP that runs in $O(2^{.67N})$ time on instances of length N .*

189 By examining the queries that this algorithm makes to MFSP, we get the following
 190 consequence regarding the perebor conjecture.

191 ► **Corollary 8** (Informal). *If brute-force is essentially optimal for solving Search-MFSP, then*
 192 *any algorithm solving MFSP can give at most an ϵ power speed up over the brute-force*
 193 *algorithm where $\epsilon = \frac{1}{7}$.*

194 **A bottom-up approach for DeMorgan formulas.** All of the results mentioned so far are
 195 proved by building an optimal formula for a function in a “top-down” way (i.e. starting from
 196 the output gate and working its way down to the tree leaves). It is natural to wonder if a
 197 “bottom-up” approach could also work.⁴

198 Indeed, we give such a bottom-up reduction for solving Search-MFSP using an oracle to
 199 MFSP that is efficient on average. Unfortunately, the guarantees we prove on the running
 200 time on this bottom-up algorithm are weaker than the guarantees provided in Theorem 4.
 201 Moreover, the proof of correctness for the algorithm requires our formulas to be DeMorgan
 202 formulas and not, say, \mathbb{B}_2 formulas. Still, we include this result because we think the algorithm
 203 is interesting and because it makes use of the following lemma (which is the part where
 204 DeMorgan formulas are crucial) that may be of independent interest. Roughly speaking, the
 205 lemma shows that optimal DeMorgan formulas must not have too large depth.

206 ► **Lemma 9** (also Lemma 54). *Suppose φ is an optimal DeMorgan formula for a function on*
 207 *n -inputs. Then the depth of φ is at most $O(\frac{2^n}{n \log n})$.*

⁴ The idea that a bottom-up approach could also be an efficient way to solve Search-MFSP was given to me by Ryan Williams.

208 **1.3 Techniques and Proof Overviews**

209 **The top-down approach.** As mentioned earlier, our reduction works in a top-down manner.
 210 We formalize this as follows. For any Boolean function f on n -inputs, we define the set
 211 $\text{OptSubcomps}(f)$ to consist of elements of the form $\{g, \nabla, h\}$ — where $g, h : \{0, 1\}^n \rightarrow \{0, 1\}$
 212 and $\nabla \in \{\wedge, \vee\}$ — satisfying the property that there exists an optimal formula φ for
 213 computing f such that $\varphi = \varphi_g \nabla \varphi_h$ where φ_g and φ_h are subformulas computing g and h
 214 respectively.

215 We can naturally define the Decomposition Problem, denoted DecompProblem as follows:

- 216 ■ **Given:** a non-trivial⁵ function f ,
- 217 ■ **Output:** some element of $\text{OptSubcomps}(f)$.

218 Our two main reductions work by solving the DecompProblem . It is easy to show that one
 219 can solve Search-MFSP efficiently by recursively calling an DecompProblem oracle to build
 220 an optimal formula gate-by-gate from top to bottom. (See Theorem 21 for details.)

221 Thus, we now focus on trying to solve DecompProblem .

222 **A high level approach to solving DecompProblem .** Our two top-down reductions will use
 223 a similar approach to solving DecompProblem . (Actually, our worst-case reduction will use
 224 three different approaches, but this will be one of them.)

- 225 1. Find an efficient “test” that functions in⁶ an optimal subcomputation of f pass, but not
 226 too many other functions pass.
- 227 2. Efficiently build the (not too long) list *Candidates* of functions that pass the “test.”
- 228 3. Iterate through all pairs of functions in *Candidates* and each possible gate, and check if
 229 this constitutes an element of $\text{OptSubcomps}(f)$.

230 We first describe how we do Item 3 since it is simpler and then describe our “test” for
 231 Item 1. Our method for Item 2 will be different in both reductions.

232 **Item 3: checking membership in $\text{OptSubcomps}(f)$.** Given access to a MFSP oracle it is
 233 actually very easy to check whether some $\{g, \nabla, h\}$ is an element of $\text{OptSubcomps}(f)$ or not.
 234 In Lemma 22 we observe that $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$ if and only if $f(x) = g(x) \nabla h(x)$
 235 for all x and $L(f) = L(g) + L(h)$.

236 **Item 1: the $\text{Select}[f, g]$ test.** The idea for our “test” is based on the gate elimination
 237 technique and the implications gate elimination has on the $\text{Select}[\cdot, \cdot]$ function defined as
 238 follows. Given functions $f, g : \{0, 1\}^n \rightarrow \{0, 1\}$, we define $\text{Select}[f, g] : \{0, 1\}^n \times \{0, 1\} \rightarrow \{0, 1\}$
 239 by

$$240 \quad \text{Select}[f, g](x, z) = \begin{cases} f(x) & , \text{ if } z = 0 \\ g(x) & , \text{ if } z = 1. \end{cases}$$

241 Our test for whether g might be part of an optimal subcomputation for f will be whether
 242 the quantity

$$243 \quad L(\text{Select}[f, g]) - L(f)$$

⁵ here by non-trivial we mean a function that cannot be computed by a formula of size one

⁶ In case it is not clear, we say a function g is *in an optimal subcomputation* for f if there exists a gate ∇ and function h such that $\{g, \nabla, h\}$ is an element of $\text{OptSubcomps}(f)$.

244 is small — in particular, no more than a parameter C . The exact value of C will depend
 245 on the reduction (we use this test in all three of our reductions with a different value for
 246 C), but to give a reader some idea, C will be an element of $\{1, n + 2, 10 \cdot \frac{2^n}{n}\}$ where n is the
 247 number of input bits f takes.

248 Now, we needed our test to have two properties:

- 249 ■ Property 1: (Validity) any function that is in an optimal subcomputation for f must pass
 250 this test, and
- 251 ■ Property 2: (Usefulness) this test does not accept too many other functions.

252 With regards to Property 1, we show in Lemma 24 that if $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$,
 253 then $L(\text{Select}[f, g]) \leq L(f) + 1$ and $L(\text{Select}[f, h]) \leq L(f) + 1$.

254 We can give the relatively straightforward proof that $L(\text{Select}[f, g]) \leq L(f) + 1$ here.
 255 Suppose that $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$. To avoid some case analysis, assume that $\nabla = \wedge$.
 256 Then there exists an optimal formula $\varphi = \varphi_g \wedge \varphi_h$ such that φ_g computes g and φ_h computes
 257 h . Then the formula $\varphi_g(x) \wedge (\varphi_h(x) \vee z)$ computes $\text{Select}[f, g](x, z)$ and has size $L(f) + 1$.

258 For Property 2, our test must be such that the set of all functions q satisfying

$$259 \quad L(\text{Select}[f, q]) - L(f) \leq C$$

260 is not too large. In Lemma 25, we show that the number of such q is bounded by

$$261 \quad O(t \cdot 2^{C-1} N \log N)$$

262 where N is the length the truth table of f and t is the number of distinct formulas (modulo
 263 an isomorphism between formulas defined in Section 2.2) computing f of size $L(f) + C - 1$.
 264 (In the case that $C = n + 2$, t is the number of “near-optimal” formulas discussed earlier in
 265 Section 1.2.)

266 The intuition behind this proof is to use gate elimination. In more detail, if φ is a formula
 267 of size $L(f) + C$ computing $\text{Select}[f, g]$, then we can set $z = 0$ in φ and eliminate between
 268 one and C gates from φ to obtain a new formula φ' of size at most $L(f) + C - 1$ computing
 269 f . Hence, we can describe φ (and hence g) by first describing φ' (a small-ish formula for f)
 270 and the gates that need to be added back to φ' in order to obtain φ .

271 While this intuition is relatively straightforward, the proof itself is surprisingly tedious.
 272 In particular, the intuition, as stated, only gives a bound with a N^C factor dependence on
 273 C . To achieve the stated bound with a 2^C factor dependence on C requires some details.
 274 Moreover, this dependence on C is important since a N^C dependence would make Theorem 4
 275 have a quasipolynomial dependence on t instead of a polynomial dependence.

276 **Our top-down deterministic reduction** We now outline how the deterministic algorithm
 277 in Theorem 4 works to solve `DecompProblem` on an input f .

278 We have already introduced the some of the ideas for the algorithm in Theorem 4. In detail,
 279 let *BestFunctions* be the set of functions that are in an optimal subcomputation of f . Let
 280 *GoodFunctions* denote the set of functions g that pass the test $L(\text{Select}[f, g]) - L(f) \leq n + 2$
 281 (for this algorithm we set $C = n + 2$). From our previous discussions, we know that the size of
 282 *GoodFunctions* can be bounded by a quantity related to the number of near-optimal formulas
 283 for f , and we know that *GoodFunctions* contains all the functions in *BestFunctions*.

284 Later we explain how to construct the list *GoodFunctions*. Note though that once
 285 the list *GoodFunctions* is constructed, we can then iterate through all pairs of functions
 286 in *GoodFunctions* and efficiently check if they yield an optimal subcomputation, as we
 287 discussed previously.

31:8 Connecting Perebor Conjectures

288 Hence, the missing piece is to efficiently enumerate the elements of *GoodFunctions*. In
289 fact, we do not quite need to enumerate *all* the elements of *GoodFunctions*. It suffices
290 to enumerate a subset, that we call *Candidates*, of *GoodFunctions* that contains all the
291 elements of *BestFunctions*. Informally, one can think of the *Candidates* subset as a set of
292 “good enough functions.”

293 The key observation is as follows. If q is a function on n -inputs and one defines the truth
294 table $T_{q,i}$ of length 2^n that is equal to q on its first i bits and equals one on the remaining
295 bits, then

$$296 \quad \mathsf{L}(T_{q,i}) \leq \mathsf{L}(q) + n + 1$$

297 since one can compute $T_{q,i}$ by computing q , computing whether the input is greater than i ,
298 and ORing these two values. The $\text{Select}[\cdot, \cdot]$ function actually respects this observation in
299 a nice way. In particular, since functions g in *BestFunctions* satisfy the stronger property
300 that $\mathsf{L}(\text{Select}[f, g]) \leq \mathsf{L}(f) + 1$, one can show that if $g \in \text{BestFunctions}$, then

$$301 \quad \mathsf{L}(\text{Select}[f, T_{g,i}]) \leq \mathsf{L}(f) + n + 2$$

302 for all i . In other words, if $g \in \text{BestFunctions}$, then $T_{g,i}$ is in *GoodFunctions* for all i .

303 Using this fact, we can construct a subset *Candidates* of *GoodFunctions* that contains all
304 the elements of *BestFunctions* by bit-by-bit extending a set of prefixes *PartialCandidates*
305 that pass our test until these prefixes become full functions. Since the prefixes of func-
306 tions in *BestFunctions* do pass our test, we will be able to discover all the functions in
307 *BestFunctions*.

308 In more detail, we start with a set *PartialCandidates* that initially only contains the
309 empty prefix. While *PartialCandidates* is non-empty, we remove a prefix γ from it and
310 try to extend it by one bit. That is, for each bit $b \in \{0, 1\}$, we consider γ_b obtained by
311 appending b to γ . We then see if the prefix γ_b “passes our test” by seeing if the truth table
312 T_{γ_b} , obtained by padding γ_b with ones until it has length 2^n , has the property

$$313 \quad \mathsf{L}(\text{Select}[f, T_{\gamma_b}]) \leq \mathsf{L}(f) + n + 2.$$

314 If so, we either add γ_b to *Candidates* or back to *PartialCandidates* depending on whether
315 the string γ_b is of length 2^n or not. We continue until *PartialCandidates* is empty. The full
316 details can be found in Algorithm 2.

317 **Our top-down randomized worst-case reduction.** The algorithm in Theorem 7 uses three
318 different strategies for finding an optimal subcomputation in the worst-case using an oracle
319 to MFSP. We give a rough overview of each of these three parts.

320 Suppose the input to the algorithm is a function f on n -inputs. First, the algorithm picks
321 $2^{2N/3}$ random formulas of size $\mathsf{L}(f)$ and checks if any of these formulas compute f . If so,
322 we are done. Otherwise, we know that the number of optimal formulas for f cannot be too
323 large (in particular, is upper bounded by roughly $2^{N/3}$ with high probability).

324 In the second part, we construct a set of candidate functions that pass a test. The
325 guarantee on the number of optimal formulas from the previous step ensures that the size of
326 the set

$$327 \quad \{g : \mathsf{L}(\text{Select}[f, g]) \leq \mathsf{L}(f) + 1\}$$

328 is bounded by $O(2^{N/3})$, and we know that all functions that are in an optimal subcomputation
329 for f are in this set. Hence, what we would like to do is enumerate the functions in this set,

330 however, the author does not know how to do this efficiently. Instead, we examine the subset
 331 of functions in this set that have not too large complexity. That is, we iterate through all
 332 functions with complexity at most $\frac{2}{3} \cdot \frac{2^n}{\log n}$ and build

$$333 \quad \text{Candidates} = \{g : \mathsf{L}(\text{Select}[f, g]) - \mathsf{L}(f) \leq 1 \text{ and } \mathsf{L}(g) \leq \frac{2}{3} \cdot \frac{2^n}{\log n}\}.$$

334 This takes time $O(2^{2N/3})$. We then try to find a pair of functions in *Candidates* that form
 335 an optimal subcomputation.

336 If we succeed, we are done. Otherwise, we know that there exists an optimal subcompu-
 337 tation $\{g, \nabla, h\}$ of f where h has complexity greater than $\frac{2}{3} \cdot \frac{2^n}{\log n}$. This also implies that g
 338 has complexity at most $(1 + o(1)) \frac{2^n}{3 \log n}$ since $\mathsf{L}(f) = \mathsf{L}(g) + \mathsf{L}(h)$ and $\mathsf{L}(f) \leq (1 + o(1)) \frac{2^n}{\log n}$.

339 In the third part, we look for such an “unbalanced” subcomputation as follows. We
 340 iterate through each g in *Candidates* with complexity at most $(1 + o(1)) \frac{2^n}{3 \log n}$ and each
 341 $\nabla \in \{\wedge, \vee\}$ and try to find a matching h by considering each h satisfying $f = g \nabla h$. We argue
 342 that this is efficient because the the set of h satisfying the constraint that $f = g \nabla h$ is not
 343 too large (in particular, of size at most $2^{N/3}$). The reason for why this set must be small is
 344 that the constraint that $f = g \nabla h$ actually forces many of the values of h to a fixed zero/one
 345 value. Indeed, we argue that a large number of values must be “forced,” since if only a small
 346 number of values of h were “forced,” then a theorem of Pippenger [16] ensures that there
 347 would be a function h of too small complexity (smaller than $\frac{2}{3} \cdot \frac{2^n}{\log n}$) that satisfied $f = g \nabla h$,
 348 which would contradict that fact that the second part of the algorithm failed.

349 **A bottom-up approach.** Our final algorithm takes a different approach than our previous
 350 reductions, working bottom-up instead of top-down. The basic idea of the bottom-up
 351 approach is as follows. Begin with the set *Candidates* of all functions computed by formulas
 352 of size one. For each pair of functions g, h in *Candidates* and each $\nabla \in \{\wedge, \vee\}$, compute the
 353 function $q = g \nabla h$. Next, see if $g \nabla h$ is an optimal formula for q using the MFSP oracle. If
 354 so, use some one-sided heuristic (that never gives an incorrect NO answer) to test if q is
 355 computed by some gate in an optimal formula for f , and add q to *Candidates* if it passes
 356 this heuristic. Repeat this process until f is added to *Candidates*, in which case one can
 357 construct an optimal formula for f by tracing back through the functions that led to it.

358 The difficulty in this approach is in finding an appropriate heuristic that significantly
 359 prunes the search space of possible candidates. A natural contender for such a heuristic, in
 360 light of our previous algorithms, is testing if $\mathsf{L}(\text{Select}[f, q]) - \mathsf{L}(f)$ is small. However, if our
 361 only guarantee is that q is computed by some gate in some optimal formula φ for f , the best
 362 upper bound we manage to prove for the quantity $\mathsf{L}(\text{Select}[f, q]) - \mathsf{L}(f)$ is linear in the depth
 363 of φ .

364 Luckily, Lemma 54 shows that the depth of φ cannot be too large. In particular, if φ
 365 is an optimal DeMorgan formula, then the depth of φ is bounded by $O(\frac{2^n}{n})$ where n is the
 366 number of inputs f takes. At a high-level, the proof of this lemma works by saying that if a
 367 formula has very large depth, then there are many small subformulas that lie along a path in
 368 the binary tree of φ . Because there are so many of these small subformulas, there must be a
 369 pair that compute the same function, and this redundancy can be eliminated to produce a
 370 slightly smaller formula.

371 Using this lemma, we show that the above bottom-up approach runs in time quadratic in
 372 the number of formulas for computing f that are within $O(\frac{2^n}{n})$ of being optimal, additively.

373 1.4 Open Questions

374 There are several intriguing questions raised by this work. Looking at our main theorem,
 375 the most obvious question is whether one can improve the bound we give on the number of
 376 near-optimal formulas for a random function. Our bound hardly seems correct, although its
 377 hard to imagine how one could do better with current techniques.

378 Perhaps an indirect approach could work. Is there any operation one can apply to a
 379 function in order to reduce the number of optimal formulas it has? It seems plausible
 380 that multiple applications of the $\text{Select}[\cdot, \cdot]$ function might cut down the number of optimal
 381 formulas.

382 Another idea would be to try to modify the heuristic “tests” in our reduction. At their
 383 heart, all our “tests” are powered by the gate elimination technique. It seems reasonable
 384 that more powerful lower bound techniques (which we indeed do have for formulas) might
 385 lead to better heuristics and thus more efficient search-to-decision reductions.

386 There is also the question this paper began with: can one prove a non-trivial exact search
 387 to decision reduction for MCSP? The difficulty in adopting our approach to MCSP is that
 388 there are just too many ways to add a single gate to a circuit, which ruins the bounds we get
 389 on the number of functions passing our $\text{Select}[f, g]$ test. Is there any way to get around this?

390 Taking a step back, one can also ask what role relativization plays in the search versus
 391 decision question. Can one show that there is an oracle relative to which MCSP or MFSP can
 392 be solved in linear time, but the corresponding search problem requires exponential time?

393 Finally, can one extend Lemma 9 to the case of formulas over \mathbb{B}_2 or even just prove a
 394 better bound for DeMorgan formulas?

395 1.5 Organization

396 In Section 2, we fix our notation and definitions, including our notion of formula isomorphism.
 397 In Section 3, we introduce the top-down approach and outline our basic strategy for solving
 398 Search-MFSP. Section 4 introduces the $\text{Select}[\cdot, \cdot]$ function and proves bounds on number of
 399 functions that pass “tests” related to the $\text{Select}[\cdot, \cdot]$ function. Section 5 gives a deterministic
 400 search to decision reduction for MFSP and shows it is efficient on average. Section 6 then
 401 gives a reduction that works in the worst case. Finally, Section 7 demonstrates a bottom-up
 402 approach for trying to solve Search-MFSP.

403 2 Preliminaries

404 For a positive integer n , we let $[n]$ denote the subset of integers $\{1, \dots, n\}$.

405 2.1 DeMorgan Formulas and Formula Size

406 Our notion of formulas will be DeMorgan formulas. A DeMorgan formula φ on n -inputs of
 407 size s is given by:

408 ■ a directed rooted binary tree on the vertex set $[2s - 1]$, specified by a subset $E_\varphi \subseteq$
 409 $[2s - 1] \times [2s - 1]$ of edges, and

410 ■ a gate labeling function $\tau_\varphi : [2s - 1] \rightarrow \{\wedge, \vee\} \cup \{0, 1, x_1, \dots, x_n, \neg x_1, \dots, \neg x_n\}$

411 where τ takes values in $\{\wedge, \vee\}$ on the internal nodes in φ and τ takes values in

412 $\{0, 1, x_1, \dots, x_n, \neg x_1, \dots, \neg x_n\}$

413 on the leaf nodes in φ . The edges in E_φ point from inputs towards outputs. We note that
 414 our definition implicitly uses the fact that a binary tree with s leaf nodes has $s - 1$ internal

415 nodes. We also note that in our definition we do not need to specify the “left” and “right”
 416 child of an internal node since our gate set $\{\wedge, \vee\}$ is made up of symmetric functions. We
 417 will define a notion of formula isomorphism in Section 2.2.

418 We will use the notation $|\varphi|$ to denote the *size* of a formula φ (i.e. the number of leaves in
 419 the binary tree underlying φ). Given a Boolean function f , we denote the *minimum formula*
 420 *size* of f by

$$421 \quad L(f) = \min\{|\varphi| : \varphi \text{ is a formula computing } f\}.$$

422 We say a formula φ is an *optimal* formula for a Boolean function f , if φ computes f and
 423 $|\varphi| = L(f)$.

424 We note, however, that all of our results except the ones presented in Section 7 apply
 425 equally well to formulas with arbitrary fan-in-two gates (i.e. the formulas over the \mathbb{B}_2 basis).
 426 Moreover, all our results hold for other size notions such as gates and wires.

427 2.2 Optimal Formulas and Formula Isomorphism

428 Since our results will depend on the number of formulas satisfying certain properties, we will
 429 be clear about when exactly we are saying formulas are distinct in our count.

430 In particular, as we have defined formulas, one can obtain many optimal formulas from a
 431 single optimal formula by relabeling the nodes in underlying binary tree.

432 Thus, it will be useful to define an isomorphism on formulas and only count formulas
 433 modulo this isomorphism. In particular, we will define two formulas to be *isomorphic* if they
 434 are isomorphic as labelled binary trees.

435 In order to properly define this, we introduce some notation. If φ is a formula of size s
 436 with an underlying edge set E_φ and a labelling function τ_φ and $\sigma : [2s - 1] \rightarrow [2s - 1]$ is a
 437 permutation, then we let $\psi = \sigma(\varphi)$ be the formula of size s whose edge set E_ψ is given by

$$438 \quad E_\psi = \{(\sigma(i), \sigma(j)) : (i, j) \in E_\varphi\}$$

439 and whose labelling function τ_ψ is given by

$$440 \quad \tau_\psi(\sigma(i)) = \tau_\varphi(i).$$

441 We say two formulas φ and φ' are *isomorphic* if $|\varphi| = |\varphi'|$ and there is a permutation σ
 442 such that $\varphi' = \sigma(\varphi)$.

443 From each equivalence class of isomorphic formulas, we pick a single representative that
 444 we call the *canonical formula* for that equivalence class. Note that for our purposes we do
 445 not need that this canonical formula to be computable, as we will just be using them in our
 446 analysis. Then we define $\text{CanonOpt}_k\text{Formulas}(f)$ to be the set of canonical formulas that are
 447 optimal for computing f up to an additive k -term.

► **Definition 10** ($\text{CanonOpt}_k\text{Formulas}(f)$).

$$448 \quad \text{CanonOpt}_k\text{Formulas}(f) = \{\varphi : \varphi \text{ is a canonical formula and } |\varphi| \leq L(f) + k\}.$$

449 2.3 MFSP, Search-MFSP and Conventions on n and N

450 We now define the *Minimum Formula Size Problem* denoted MFSP.

► **Definition 11** (MFSP). We define the problem MFSP as follows

452 ■ **Given:** a truth table of a Boolean function f and an integer size parameter $s \geq 1$

31:12 Connecting Porebor Conjectures

453 ■ **Determine:** if $L(f) \leq s$.

454 We define the search version of MFSP analogously.

455 ► **Definition 12** (Search-MFSP). Search-MFSP is the problem defined as follows:

456 ■ **Given:** a truth table of a Boolean function f

457 ■ **Output:** a formula φ of size $L(f)$ computing f .

458 We note that $\text{MFSP} \in \text{NP}$ since given a minimum-sized formula as a witness, one can
459 check that this indeed computes f efficiently since the truth table of f is provided and every
460 function has a formula of size at most the length of its truth table (see Theorem 14).

461 When describing a function f that is an input to MFSP, one naturally wants to denote
462 by n two different quantities: the number of variable inputs to a function f and the length of
463 the truth table of f (which is the true input length for MFSP). We maintain the convention
464 throughout this paper that n denotes the input arity of f and $N = 2^n$ denotes the length of
465 the truth table of f .

466 2.4 Useful Facts About Formulas

467 We will make use of some basic facts about formulas in our work. First, one can easily bound
468 the number of formulas of size at most s .

469 ► **Proposition 13.** *The number of formulas on n -inputs of size at most s is at most*
470 $2^{s \log n(1+O(1/\log n))}$

471 We also know tight upper bounds on the maximum formula complexity of a n -input
472 function.

473 ► **Theorem 14** (Lozhkin [11] improving on Lupanov [12]). *Let $f : \{0, 1\}^n \rightarrow \{0, 1\}$. Then*

$$474 \quad L(f) \leq \frac{2^n}{\log n} \left(1 + O\left(\frac{1}{\log n}\right)\right)$$

475 Combining the size upper bound in Theorem 14 with the bound on the number of formulas
476 of size s , we get the following proposition.

477 ► **Proposition 15** (Random functions have not too many near optimal formulas). *Let n and*
478 *k be positive integers. Let $N = 2^n$. Assume $k = O\left(\frac{2^n}{\log^2 n}\right)$. Then all but a $o(1)$ -fraction of*
479 *n -input Boolean functions f satisfy*

$$480 \quad |\text{CanonOpt}_k \text{Formulas}(f)| = 2^{O\left(\frac{N}{\log \log N}\right)}.$$

481 **Proof.** Theorem 14 says that every n -input function has a formula of size at most

$$482 \quad \frac{2^n}{\log n} \left(1 + O\left(\frac{1}{\log n}\right)\right).$$

483 Thus, any formula for computing n -input function that is within an additive k of being
484 optimal has size at most s where

$$485 \quad s \leq k + \frac{2^n}{\log n} \left(1 + O\left(\frac{1}{\log n}\right)\right) = \frac{2^n}{\log n} \left(1 + O\left(\frac{1}{\log n}\right)\right).$$

486 Proposition 13 implies that the number of formulas of size at most s is upper bounded by

$$487 \quad 2^{s \log n(1+o(1))} = 2^{N(1+O\left(\frac{1}{\log \log N}\right))}.$$

488 Hence, since there are 2^N Boolean functions on n -inputs, it follows that in expectation a
 489 random function has at most

$$490 \quad 2^{O\left(\frac{N}{\log \log N}\right)}$$

491 formulas within k of being optimal. The desired claim then follows by an application of
 492 Markov's inequality. \blacktriangleleft

493 We note that the bound given by Proposition 15 is actually counting formulas that are
 494 isomorphic to each other as distinct. Unfortunately removing this redundancy does not
 495 improve on the bound in Proposition 15. However, the fact that our results rely on the
 496 number of distinct formulas up to isomorphism means that there is no obvious obstruction
 497 to better bounds being proved and hence to our algorithms being more efficient.

498 We will also make use of the fact that integer comparison can be implemented by
 499 linear-sized formulas.

500 **► Proposition 16** (Small formulas for integer comparison). *Let $y \in \{0, 1\}^n$. Let $GrtrThan_y :$
 501 $\{0, 1\}^n \rightarrow \{0, 1\}$ be the function given by $GrtrThan_y(x) = 1$ if and only if $x > y$ in the usual
 502 lexicographic order on $\{0, 1\}^n$. Then $L(GrtrThan_y(x)) \leq n$.*

503 **Proof.** We work by induction on n . If $n = 1$, then clearly $L(GrtrThan_y) = 1$ (either it is 0
 504 if $y = 1$ or it equals x if $y = 0$).

505 Now suppose $n > 1$. Let x_1, \dots, x_n and y_1, \dots, y_n denote the bits of x and y respectively
 506 where x_1 and y_1 denotes the highest order bit. Let $x', y' \in \{0, 1\}^{n-1}$ be given by $x' = x_2 \dots x_n$
 507 and $y' = y_2 \dots y_n$ respectively.

508 If $y_1 = 1$, then

$$509 \quad x > y \iff (x_1 = 1) \wedge (x' > y').$$

510 if $y_1 = 0$, then

$$511 \quad x > y \iff (x_1 = 1) \vee (x' > y').$$

512 In either case, we get by induction that $L(GrtrThan_y) \leq 1 + n - 1 = n$. \blacktriangleleft

513 2.5 Partial Functions and their Formula Size

514 Partial functions will be a crucial building block in our reductions. A *partial Boolean function*
 515 is a function $\gamma : \{0, 1\}^n \rightarrow \{0, 1, ?\}$ for some integer $n \geq 1$. We denote partial functions using
 516 Greek letters such as γ and μ , although sometimes we resort to the Roman alphabet with a
 517 ? subscript such as $h_?$.

518 In contrast, we say a Boolean function $f : \{0, 1\} \rightarrow \{0, 1\}$ is *total* Boolean function
 519 (though we allow for a partial Boolean function to indeed be total).

520 We say a total Boolean function g *agrees* with a partial Boolean function γ if for all x

$$521 \quad \gamma(x) \in \{0, 1\} \implies \gamma(x) = g(x).$$

522 One can naturally define the minimum formula size of a partial Boolean function γ as
 523 follows

$$524 \quad L(\gamma) = \min\{L(g) : g \text{ is a total function that agrees with } \gamma\}.$$

525 The following theorem bounding the formula complexity of partial functions will be useful
 526 in our randomized worst-case reduction.

31:14 Connecting Peregbor Conjectures

527 ► **Theorem 17** (Pippenger [16]). Let $\gamma : \{0, 1\}^n \rightarrow \{0, 1, ?\}$ be a partial function. Let
528 $p_? = \frac{|\gamma^{-1}(?)|}{2^n}$. Then,

$$529 \quad L(\gamma) \leq (1 + o(1)) \cdot (1 - p_?) \frac{2^n}{\log n}.$$

530 **3** The Top-Down Approach

531 Our two main reductions both take a “top-down” approach to finding an optimal formula.
532 That is, given a function f , they try to find functions g and h such that g and h are the two
533 functions fed into the final output gate in an optimal formula for f and then recursing.

534 This is formalized as follows.

535 ► **Definition 18** (Optimal Subcomputations Set). Let $f : \{0, 1\}^n \rightarrow \{0, 1\}$. We define the set
536 of optimal subcomputations for f , denoted $\text{OptSubcomps}(f)$, as follows.

537 Let $g, h : \{0, 1\}^n \rightarrow \{0, 1\}$ be Boolean functions of the same arity as f and $\nabla \in \{\wedge, \vee\}$.
538 Then $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$ if and only if there exists an optimal formula $\varphi = \varphi_g \nabla \varphi_h$
539 for computing f such that φ_g computes g and φ_h computes h .

540 We note that in this definition we are implicitly using that the gate set $\{\wedge, \vee\}$ is symmetric
541 with respect to its inputs.

542 We say a function g is in an optimal subcomputation for f if g is contained in some
543 element of $\text{OptSubcomps}(f)$. In other words, g is in an optimal subcomputation for f if there
544 exists an h and ∇ such that $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$.

545 It is easy to see that $\text{OptSubcomps}(f)$ is almost always non-empty.

546 ► **Proposition 19.** Let $f : \{0, 1\}^n \rightarrow \{0, 1\}$ such that $L(f) \geq 2$. Then $\text{OptSubcomps}(f)$ is
547 non-empty.

548 Next, we can define the problem of finding an optimal subcomputation.

549 ► **Definition 20** (Decomposition Problem). The Decomposition Problem, DecompProblem is
550 as follows:

- 551 ■ **Given:** the truth table of a Boolean function f satisfying $L(f) \geq 2$
- 552 ■ **Output:** some element of $\text{OptSubcomps}(f)$.

553 It is easy to see that DecompProblem is equivalent to Search-MFSP . DecompProblem can
554 be easily solved with an oracle to Search-MFSP . The following recursive procedure shows
555 the reverse direction.

556 ► **Theorem 21** (Search-MFSP reduces to DecompProblem). There is a deterministic $O(N^2)$ -
557 time algorithm for solving Search-MFSP on inputs of length N given access to an oracle that
558 solve DecompProblem on instances of length N .

559 The pseudocode for this reduction is written in Algorithm 1, which we recommend the
560 reader look at before proceeding.

561 The correctness of this algorithm is easy to see as long as one is able to bound the number
562 of recursive calls the algorithm makes. To see that the number of recursive calls is bounded
563 by $O(N)$, notice that each iteration of the algorithm reveals one more gate in the optimal
564 formula for f . Thus, since $L(f) = O(N)$, we have that there are at most $O(N)$ recursive
565 calls. ◀

■ **Algorithm 1** Reduction from Search-MFSP to DecompProblem

Proof. **procedure** FINDOPTFORMULA(f)

 ▷ Given the length- N truth table of a function f that takes n -inputs and oracle access to DecompProblem return an optimal formula for f .

if there exists a size one formula φ computing f **then**

return φ .

end if

 Let $\{g, \nabla, h\}$ be the output returned by the oracle DecompProblem(f).

 Recursively compute the formula $\varphi_g \leftarrow \text{FindOptFormula}(g)$.

 Recursively compute the formula $\varphi_h \leftarrow \text{FindOptFormula}(h)$.

return the formula given by $\varphi_g \nabla \varphi_h$.

end procedure

566 Our goal is now to try to solve DecompProblem (i.e. find an element of $\text{OptSubcomps}(f)$)
 567 given an oracle to MFSP. Recall from the introduction that our high-level approach is as
 568 follows

- 569 1. Find an efficient “test” that functions that in an optimal subcomputation of f pass but
 570 not too many other functions pass.
- 571 2. Efficiently build the (not too long) list *Candidates* of things that pass the test.
- 572 3. Iterate through all pairs of elements in *Candidates* and all possible gates, and efficiently
 573 check if this yields an element of $\text{OptSubcomps}(f)$.

574 Item 1 will be the subject of Section 4, Item 2 will be different in our two main reductions,
 575 and Item 3 is provided by the next lemma.

576 ► **Lemma 22** (Test membership in $\text{OptSubcomps}(f)$ efficiently with MFSP). *Let $f, g, h : \{0, 1\}^n \rightarrow \{0, 1\}$, and let $\nabla \in \{\wedge, \vee\}$. Then*

578 $\{g, \nabla, h\} \in \text{OptSubcomps}(f) \iff f = g \nabla h \text{ and } L(f) = L(g) + L(h)$.

579 **Proof.** We prove the forward direction first. Suppose that $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$.
 580 Then there exists an optimal formula $\varphi = \varphi_g \nabla \varphi_h$ for computing f such that φ_g computes
 581 g and φ_h computes h . Clearly this implies that $f = g \nabla h$. Consequently, we know that
 582 $L(f) \leq L(g) + L(h)$.

583 On the other hand, since φ is an optimal formula for f , we have that

584 $L(f) = |\varphi| = |\varphi_g| + |\varphi_h| \geq L(g) + L(h)$.

585 Combining the two inequalities on $L(f)$, we get that $L(f) = L(g) + L(h)$. This completes the
 586 forward direction.

587 For the reverse direction, suppose that $L(f) = L(g) + L(h)$ and $f = g \nabla h$. Let φ_g and φ_h
 588 be optimal formulas for g and h . Then $\varphi = \varphi_g \nabla \varphi_h$ clearly computes f and has size $L(f)$.
 589 Hence $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$. ◀

590 **4 Using gate elimination to find functions in an optimal**
 591 **subcomputation**

592 Our approach to solving DecompProblem involves finding a “test” that functions in an optimal
 593 subcomputation pass but not too many other functions pass. The test will be based off the
 594 following function.

31:16 Connecting Peregbor Conjectures

595 ► **Definition 23** ($\text{Select}[\cdot, \cdot]$). Let $f, g : \{0, 1\}^n \rightarrow \{0, 1\}$. We define the function $\text{Select}[f, g] :$
 596 $\{0, 1\}^n \times \{0, 1\} \rightarrow \{0, 1\}$ by

$$597 \quad \text{Select}[f, g](x, z) = \begin{cases} f(x) & , \text{ if } z = 0 \\ g(x) & , \text{ if } z = 1 \end{cases}$$

598 We emphasize that $\text{Select}[f, g]$ function is only defined when f and g have the same arity.
 599 Now, our “test” will be to see if the quantity

$$600 \quad L(\text{Select}[f, g]) - L(f)$$

601 is small (how small will depend on our reduction).

602 Indeed, for functions in an optimal subcomputation, this quantity is exactly one!⁷

603 ► **Lemma 24.** Suppose g is in an optimal subcomputation for f . Then

$$604 \quad L(\text{Select}[f, g]) \leq L(f) + 1.$$

605 **Proof.** Since g is in an optimal subcomputation for f , there exists an optimal formula
 606 $\varphi = \varphi_g \nabla \varphi_h$ such that φ_g computes g . If $\nabla = \wedge$, then

$$607 \quad \varphi_g \wedge (\varphi_h \vee z)$$

608 is a formula for $\text{Select}[f, g]$ of size $L(f) + 1$. Otherwise $\nabla = \vee$. Then

$$609 \quad \varphi_g \vee (\varphi_h \wedge \neg z)$$

610 is a formula for $\text{Select}[f, g]$ of size $L(f) + 1$. ◀

611 On the other hand, the number of functions that “pass this test” can be upper bounded
 612 in terms of $|\text{CanonOpt}_k \text{Formulas}(f)|$.

613 ► **Lemma 25.** Let k be a positive integer. Let $f : \{0, 1\}^n \rightarrow \{0, 1\}$. Assume $L(f) \geq 2$. Let
 614 $\text{TestPassers} = \{g : L(\text{Select}[f, g]) - L(f) \leq k + 1\}$. Then

$$615 \quad |\text{TestPassers}| \leq O(|\text{CanonOpt}_k \text{Formulas}(f)| \cdot 2^k N \log N)$$

616 where $N = 2^n$.

617 **Proof.** At a high-level the idea is that, given a formula φ of size $L(f) + k + 1$ for computing
 618 $\text{Select}[f, g]$, one can replace the z -leaves in φ with 0-leaves to obtain a formula φ' of size
 619 $L(f) + k + 1$ for computing f with at least one constant leaf. One can then use a careful gate
 620 elimination argument to remove precisely one constant leaf from φ' to obtain a formula φ''
 621 that still computes f but has size $L(f) + k$. On the other hand, one can reverse this process
 622 by adding some constant leaf and gate to φ'' and then replacing some subset of the constant
 623 leaves by z -leaves.

624 This gives us a way to describe any g that passes the test, and thus allows us to bound
 625 the number of such g . In our bound, the $O(|\text{CanonOpt}_k \text{Formulas}(f)|)$ factor corresponds to
 626 the choices for φ'' , the $O(N \log N)$ corresponds to the number of ways to add a new constant
 627 leaf and gate to φ'' in order to obtain φ' , and the $O(2^k)$ factor comes from the number of

⁷ We will only prove that it is at most one, but the reader can check that if $g \neq f$ that a gate elimination argument actually implies equality.

ways to chose a subset of the (at most k) 0-leaves in φ' into z -leaves. This completes our overview of the proof.

Starting in the next paragraph, we will give the details of this proof. We caution the reader that this proof is rather long and tedious, especially compared to the intuition above. The length and detail mainly come from two sources: first, in order to show that the bound only cares about the number of *canonical* formulas (and ignores isomorphic formulas), we must careful define our intermediate operations in a way that it should be relatively clear that they respect isomorphisms; second, we must be careful in our gate elimination argument to remove precisely one leaf. Usually in a gate elimination argument, one would like to remove as many gates/leaves as possible, but in our case, since we will have to describe how to "re-add" each gate we eliminate, it is better to keep the number of eliminations to a minimum. Indeed, if we eliminated k gates, there might be roughly N^k ways to add k possible gates back, which would lead to a quasipolynomial bound when $k = n = \log N$.

Details: We prove this statement by giving two injections. For our first injection, let P denote the set of canonical formulas computing f with size exactly $L(f) + k + 1$ and with at least one constant-labelled leaf node in the formula.

We will give an injection from *TestPassers* to $P \times [2^{k+1}]$. Before defining our injection, we will need the following claims and definitions.

▷ **Claim 26.** Suppose φ computes $\text{Select}[f, g]$ and $f \neq g$, then φ has at least one leaf node labelled by z or $\neg z$.

Proof. If φ does not have any $\{z, \neg z\}$ labelled leaves, then the output of φ does not depend on z . But this contradicts that φ computes $\text{Select}[f, g]$ since $\text{Select}[f, g]$ does depend on the z input because $f \neq g$. ◁

▷ **Claim 27.** Suppose $\varphi \in P$. Then φ has at most $(k + 1)$ -many leaf nodes labelled by constants $\{0, 1\}$.

Proof. Since $\varphi \in P$, we know that $|\varphi| = L(f) + k + 1$ and φ computes f . Since $L(f) \geq 2$, we know that $|\varphi| \geq k + 3$.

If φ had more than $(k + 1)$ -many constant labelled leaves, it follows by a standard gate elimination argument (note here it is important that $|\varphi| \geq k + 3$) that there is a φ' that computes the same function as φ such that

$$|\varphi'| < |\varphi| - (k + 1) < L(f).$$

But then φ would be a formula of size less than $L(f)$ computing f which is a contradiction. ◁

We will also need the following definitions. Given a formula φ that can take z -variables as input, we define $\text{Substitute}_{z=0}(\varphi)$ to be the formula φ' given by replacing the z -labeled leaves in φ with 0-labels and replacing the $(\neg z)$ -labeled leaves in φ with 1-labels.

We note that the $\text{Substitute}_{z=0}$ operation in some sense respects formula isomorphisms.

▷ **Claim 28.** Let φ be a formula of size s that takes a z -variable as input. Let $\sigma : [2s - 1] \rightarrow [2s - 1]$ be a permutation. Then

$$\sigma \circ \text{Substitute}_{z=0}(\varphi) = \text{Substitute}_{z=0} \circ \sigma(\varphi)$$

Proof. The proof is essentially just applying the definition to both sides and seeing that the resulting edge sets and labelling functions are equal. ◁

31:18 Connecting Perebor Conjectures

670 We can also define a reverse operation to $\text{Substitute}_{z=0}$ as follows. Given a formula φ and a
 671 subset S of leaf nodes in φ that are labelled by constants $\{0, 1\}$, define $\text{Unsubstitute}_{z=0}(\varphi', S)$
 672 to be the formula φ given by replacing 0-labeled leaves in S with z -labels leaves and by
 673 replacing 1-labeled leaves in S with $(\neg z)$ -labels.

674 Indeed, the following claim whose proof we omit is easy to see.

675 \triangleright **Claim 29.** For all formulas φ there exists a set S such that

$$676 \quad \varphi = \text{Unsubstitute}_{z=0}(\text{Substitute}_{z=0}(\varphi), S).$$

677 Being more precise, S is a subset of the leaf nodes in $\text{Substitute}_{z=0}(\varphi)$ that are labelled by
 678 constants.

679 Now we are ready to describe our injection from $\text{TestPassers} \rightarrow P \times [2^{k+1}]$ on an input
 680 $g \in \text{TestPassers}$. Since $g \in \text{TestPassers}$, there is a φ of size $L(f) + k + 1$ computing
 681 $\text{Select}[f, g]$. Let $\varphi' = \text{Substitute}_{z=0}(\varphi)$. Clearly φ' computes f since φ computes $\text{Select}[f, g]$.
 682 Let $\overline{\varphi'}$ denote the canonical formula isomorphic to φ' . Then there exists a permutation σ
 683 such that

$$684 \quad \begin{aligned} \overline{\varphi'} &= \sigma(\varphi') \\ 685 \quad &= \sigma \circ \text{Substitute}_{z=0}(\varphi) \\ 686 \quad &= \text{Substitute}_{z=0} \circ \sigma(\varphi) \end{aligned}$$

688 where the last equality comes from Claim 28. Thus, using Claim 29, we know that there
 689 exists a subset S of the leaf nodes of $\overline{\varphi'}$ labelled by constants such that

$$690 \quad \text{Unsubstitute}_{z=0}(\overline{\varphi'}, S) = \sigma(\varphi).$$

691 Moreover, the set S can be viewed as an element of $[2^{k+1}]$ because $\overline{\varphi'}$ has at most $k + 1$
 692 leaf nodes labelled by constants. In particular, by construction, we have that

$$693 \quad |\overline{\varphi'}| = |\varphi'| = |\varphi| = L(f) + k + 1,$$

694 and that $\overline{\varphi'}$ computes f , so Claim 27 ensures that φ' has at most $k + 1$ many leaf nodes
 695 labelled by constants.

696 We define the output of our injection from TestPassers to $P \times [2^{k+1}]$ on input $g \in$
 697 TestPassers to be $(\overline{\varphi'}, S)$.

698 We must prove that this is indeed an injection. Towards this end, we claim that
 699 $\text{Unsubstitute}_{z=0}(\overline{\varphi'}, S)$ is a formula computing $\text{Select}[f, g]$. From this claim it is easy to see
 700 that this must be an injection.

701 \triangleright **Claim 30.** $\text{Unsubstitute}_{z=0}(\overline{\varphi'}, S)$ is a formula computing $\text{Select}[f, g]$.

702 *Proof.* S was chosen so that

$$703 \quad \text{Unsubstitute}_{z=0}(\overline{\varphi'}, S) = \sigma(\varphi).$$

704 Thus, $\text{Unsubstitute}_{z=0}(\overline{\varphi'}, S)$ computes the same function as $\sigma(\varphi)$ which in turn computes
 705 the same function as φ , which computes $\text{Select}[f, g]$ as desired. \triangleleft

706 From this injection, we get that

$$707 \quad |\text{TestPassers}| \leq 2^{k+1} \cdot |P|.$$

708 Next, we give an injection from P to the set

$$709 \text{ CanonOpt}_k \text{Formulas}(f) \times [2L(f)] \times \{\wedge, \vee\} \times \{0, 1, x_1, \dots, x_n, \neg x_1, \dots, \neg x_n\}.$$

710 To do this we will define an operation $\text{DropLeaf}(\varphi, i)$ that takes as input a formula φ of
711 size $s \geq 2$ and a leaf node $i \in [2s - 1]$ from φ and outputs the formula φ' given as follows.

712 We will first describe φ' informally and then give the formal description. φ' is obtained
713 by deleting the leaf node i and making the output of the internal node i_p that i fed into
714 simply the other node that was being fed into i_p .

715 Now, we formally describe φ' . Let $i_p \in [2s - 1]$ be the internal node that i has an edge
716 to in φ (we know this exists because $|\varphi| \geq 2$). If needed, apply a permutation to φ to obtain
717 an isomorphic formula where $i = 2s - 1$ and $i_p = 2s - 2$. Let $u \in [2s - 3]$ be the other node
718 in φ that feeds into i_p . Let φ' be the formula given by the edge set

$$719 E' = (E \cap ([2s - 3] \times [2s - 3])) \cup \{ (u, i_{pp}) : i_p \text{ feeds into } i_{pp} \text{ in } \varphi \}$$

720 and the labelling function

$$721 \tau' = \tau|_{[2s-3]}.$$

722 For example if $\varphi = (x_1 \vee x_2) \wedge x_3$ and 1 was then index of the x_1 leaf, then $\text{DropLeaf}(\varphi, 1) =$
723 $x_2 \wedge x_3$.

724 We show this operation in some sense commutes with formula isomorphisms.

725 \triangleright **Claim 31.** Let φ be formula of size s . Let i be the index a leaf node in φ , and let
726 $\sigma : [2s - 3] \rightarrow [2s - 3]$ be a permutation. Then there exists an integer i' and a permutation
727 $\sigma' : [2s - 1] \rightarrow [2s - 1]$ such that

$$728 \text{DropLeaf}(\sigma'(\varphi), i') = \sigma \circ \text{DropLeaf}(\varphi, i)$$

729 **Proof.** From our definition of $\text{DropLeaf}(\cdot, \cdot)$, we can assume without loss of generality that
730 $i = 2s - 1$ and that the internal node that i feeds into in φ is $i_p = 2s - 2$.

731 Then the claim follows from letting σ be equal to σ' on $[2s - 3]$ and letting σ be the
732 identity on $\{2s - 2, 2s - 1\}$ and applying the various definitions. \triangleleft

733 We can also define a kind of inverse operation AddLeaf function that takes the following
734 four inputs

- 735 ■ a formula φ' on n -inputs of size s ,
- 736 ■ a node i in the tree given by φ' ,
- 737 ■ a gate $\nabla \in \{\wedge, \vee\}$, and
- 738 ■ a leaf label $\ell \in \{0, 1, x_1, \dots, x_n, \neg x_1, \dots, \neg x_n\}$,

739 and outputs the formula φ of size $s + 1$ given as follows. First, we give an informal description
740 and then given a formal definition.

741 Intuitively, AddLeaf is adding a new ∇ -gate into φ' between the i -node and wherever i
742 was being output to (if i has an output), whose other input is a new ℓ -labeled leaf.

743 We define φ formally as follows. We will use the index $2s + 1$ to add in our new leaf
744 and the index $2s$ to add in our new gate. The edge set E_φ of φ is given by taking $E_{\varphi'}$ and
745 adding in the edges $(2s + 1, 2s)$ and $(i, 2s)$ and then, if there is a node i_p that i feeds into in
746 φ' , adding in an edge $(2s, i_p)$ and removing the (i, i_p) edge. The node labelling τ_φ of φ is
747 given by

$$748 \tau_\varphi(i) = \begin{cases} \tau_{\varphi'}(i) & , \text{ if } i \in [2s - 1] \\ \nabla & , \text{ if } i = 2s \\ \ell & , \text{ if } i = 2s + 1 \end{cases}$$

31:20 Connecting Perebor Conjectures

749 It is easy to see that AddLeaf can reverse a $\text{DropLeaf}(\cdot, \cdot)$ operation.

750 \triangleright **Claim 32.** Let φ be a formula of size at least two. Let i be the index of a leaf
751 node in φ . Then there exists an integer j , a gate $\nabla \in \{\wedge, \vee\}$, and a leaf label $\ell \in$
752 $\{0, 1, x_1, \dots, x_n, \neg x_1, \dots, \neg x_n\}$ such that

$$753 \quad \text{AddLeaf}(\text{DropLeaf}(\varphi, i), j, \nabla, \ell) = \varphi$$

754 One of the main steps in our injection will be provided by the following claim.

755 \triangleright **Claim 33.** Let $\varphi \in P$. Then there is an i such that $\varphi' = \text{DropLeaf}(\varphi, i)$ is a size $(L(f) + k)$
756 formula for computing f .

757 **Proof.** Let $\varphi \in P$. Then there is some internal node j in φ that takes as input a leaf node
758 indexed by i which is labelled by a constant, that is, satisfying $\tau_\varphi(i) = b \in \{0, 1\}$. We will
759 assume $b = 0$ (the proof in the $b = 1$ case is similar).

760 Let φ_j be the the subformula computed at node j , and let $\nabla_j = \tau_\varphi(j) \in \{\wedge, \vee\}$ be the
761 gate label of j . We already know that the i th leaf node feeds into φ_j . Let k be the index of
762 the other node feeding into j , and let φ_k be the subformula computed at node k . We split
763 into cases depending on whether ∇_j is an \wedge -gate or a \vee -gate.

764 First, let us suppose ∇_j is a \vee -gate. Then the formula φ_j as a function is equivalent
765 to the formula $0 \vee \varphi_k$ which is equivalent as a function to φ_k . Hence it follows that
766 $\varphi' = \text{DropLeaf}(\varphi, i)$ is an $(L(f) + k)$ -size formula (since we removed the i th leaf) computing
767 f (since φ_j and φ_k compute the same function).

768 Now, suppose that it is a \wedge -gate. Then the output of φ_j is always zero. Since $|\varphi_j| \geq 2$,
769 there exists some subformula φ_2 of φ_j of size 2 (i.e. there is some node in φ_2 that has two
770 leaves as children and φ_2 is the subformula computed at that node). Since φ_2 has two leaves,
771 there exists one leaf node index i' in φ_2 such that $i' \neq i$ (i.e. this leaf node is not the i th leaf
772 node we were considering before).

773 Then we claim that $\varphi' = \text{DropLeaf}(\varphi, i')$ is an $(L(f) + k)$ -size formula computing f . It
774 is easy to see that $|\varphi'|$ is an $(L(f) + k)$ -size formula since we removed the i' th leaf node.
775 To see that φ' still computes f , note that the 0-labeled i th leaf node in φ still exists in
776 φ' . If the gate node j was removed by the $\text{DropLeaf}(\cdot, \cdot)$ operation, then the output wire
777 of φ_j that computed the 0 function in φ has been replaced by the 0-leaf i in φ' which still
778 computes the 0 function, so φ' must still compute f . If the gate node v was not removed by
779 the $\text{DropLeaf}(\cdot, \cdot)$ operation, then the output corresponding gate to v in φ' is still computing
780 0 (since it is an \wedge -gate with a 0 input), so φ' still computes f . \triangleleft

781 Now we can finally describe the injection from P to the set

$$782 \quad \text{CanonOpt}_k \text{Formulas}(f) \times [2L(f) + 2k - 1] \times \{\wedge, \vee\} \times \{0, 1, x_1, \dots, x_n, \neg x_1, \dots, \neg x_n\}.$$

783 Given an input φ in P , we have by Claim 33 that there exists a least i -value such that
784 $\varphi' = \text{DropLeaf}(\varphi, i)$ is a formula computing f of size $L(f) + k$. Let $\overline{\varphi'}$ be the canonical
785 formula isomorphic to φ' . Then we have that $\overline{\varphi'} \in \text{CanonOpt}_k \text{Formulas}(f)$ and we have that
786 there are permutations σ and σ' and an integer i' such that

$$787 \quad \begin{aligned} \overline{\varphi'} &= \sigma(\varphi') \\ 788 \quad &= \sigma \circ \text{DropLeaf}(\varphi, i) \\ 789 \quad &= \text{DropLeaf}(\sigma'(\varphi), i') \end{aligned}$$

791 where the last equality comes from Claim 31.

792 Hence, by Claim 32, we have that there exists a gate index $j \in [2L(f) + 2k - 1]$, a gate
793 $\nabla \in \{\wedge, \vee\}$, and a leaf label $\ell \in \{0, 1, x_1, \dots, x_n, \neg x_1, \dots, \neg x_n\}$ such that

$$794 \quad \text{AddLeaf}(\overline{\varphi'}, j, \nabla, \ell, D) = \sigma'(\varphi).$$

795 In other words, $\text{AddLeaf}(\overline{\varphi'}, j, \nabla, \ell, D)$ outputs a formula isomorphic to φ .

796 Thus, we set the output of the injection on input φ to be $(\overline{\varphi'}, j, \nabla, \ell, D)$. The fact that
797 this is an injection from P is ensured by the fact that $\text{AddLeaf}(\overline{\varphi'}, j, \nabla, \ell, D)$ is isomorphic to
798 φ and the fact that P contains only canonical formulas.

799 Hence, we get that

$$800 \quad |P| \leq |\text{CanonOpt}_k \text{Formulas}(f)| \cdot 2(L(f) + k) \cdot 2 \cdot (2n + 1)$$

$$801 \quad \leq O(|\text{CanonOpt}_k \text{Formulas}(f)|(N + k) \log N).$$

803 Combining this with upper bound on TestPassers in terms of P , we get that

$$804 \quad |\text{TestPassers}| \leq O(|\text{CanonOpt}_k \text{Formulas}(f)| \cdot 2^k N \log N)$$

805

806 **5 A deterministic reduction that works on average**

807 We will now use the tools developed in Section 3 and Section 4 to give a search to decision
808 reduction that is efficient on functions with few near-optimal formulas.

809 **► Theorem 34.** *There is a deterministic algorithm solving Search-MFSP on inputs of length*
810 *N given access to an oracle that solves MFSP on instances of length $2N$ that runs in time*
811 *$O(|\text{CanonOpt}_{n+1} \text{Formulas}(f)|^2 \cdot N^5 \log^2 N)$ where $n = \log N$.*

812 Before we prove Theorem 34, we state a corollary that follows from the bound on the
813 size of $\text{CanonOpt}_k \text{Formulas}(f)$ for a random function given in Proposition 15.

814 **► Corollary 35.** *There is a deterministic algorithm solving Search-MFSP on inputs of length*
815 *N given access to an oracle that solves MFSP on instances of length at most $2N$ that runs*
816 *in time $2^{O(\frac{N}{\log \log N})}$ on all but a $o(1)$ -fraction of instances.*

817 **Proof of Corollary 35.** The algorithm for this corollary is obtained by combining the al-
818 gorithm in Theorem 34 for DecompProblem with the oracle algorithm in Theorem 21, which
819 that one can solve Search-MFSP in a recursive manner given an oracle to DecompProblem .

820 There is some subtlety in showing this algorithm yields the desired average-case efficiency,
821 however. One would like to appeal to Proposition 15, which bounds $|\text{CanonOpt}_{n+1} \text{Formulas}(f)|$
822 by $2^{O(\frac{N}{\log \log N})}$ for a random function, in order to say that this gives us an algorithm for solving
823 Search-MFSP that runs in time $2^{O(\frac{N}{\log \log N})}$ on all but a $o(1)$ -fraction of instances. However,
824 the algorithm in Theorem 21 for solving Search-MFSP requires solving DecompProblem on
825 functions other than the original input f .

826 Luckily, looking at the code for the recursive algorithm in Theorem 21, any function g
827 that we need to recursively solve DecompProblem on has that property that g is computed
828 by some gate in an optimal formula for f . It follows that the $|\text{CanonOpt}_g \text{Formulas}(n + 1)| \leq$
829 $|\text{CanonOpt}_f \text{Formulas}(n + 1)|$ since one can create a near-optimal formula for f by taking the
830 optimal formula for f that computes g at some gate and replacing the subformula at that
831 gate with a near-optimal formula for g .

832 Thus, Proposition 15 ensures that on all but a $o(1)$ -fraction of functions f , we can
833 answer all the recursive calls to DecompProblem in time $2^{O(\frac{N}{\log \log N})}$ using the algorithm in
834 Theorem 34. ◀

31:22 Connecting Perebor Conjectures

835 **Proof of Theorem 34.** We provide the pseudocode of our `DecompProblem` algorithm in Algorithm 2, which we recommend the reader look at before proceeding.

■ **Algorithm 2** A deterministic search to decision reduction for MFSP whose run time depends on the number of “near-optimal formulas”

```

1: procedure OPTIMALSUBCOMPUTATION( $f$ )
  ▷ Given the length- $N$  truth table of a function  $f$  that takes  $n$ -inputs with  $L(f) \geq 2$ , this
  procedure returns an element  $\{g, \nabla, h\}$  of OptSubcomps( $f$ ).
2:
3: Part 1: Building a Candidates list
4:   Let  $allUnknown : \{0, 1\}^n \rightarrow \{0, 1, ?\}$  be given by  $allUnknown(x) = ?$  for all  $x$ .
5:   Set  $PartialCandidates_{(0)} = \{allUnknown\}$ .
6:   Set  $i = 0$ .
7:   while  $i < N$  do
8:     Set  $PartialCandidates_{(i+1)} = \emptyset$ .
9:     for all  $\gamma \in PartialCandidates_{(i)}$  and for all  $b \in \{0, 1\}$  do
10:      Let  $x^*$  be the lexicographically first input satisfying  $\gamma(x^*) = ?$ .
11:      Let  $\gamma_b : \{0, 1\}^n \rightarrow \{0, 1, ?\}$  be given by  $\gamma_b(x) = \begin{cases} b & , \text{ if } x = x^* \\ \gamma(x) & , \text{ otherwise.} \end{cases}$ 
12:      Let  $g_{\gamma_b}$  be the (total) function given by  $g_{\gamma_b}(x) = \begin{cases} 1 & , \text{ if } \gamma_b(x) = ? \\ \gamma_b(x) & , \text{ otherwise.} \end{cases}$ 
13:      if  $L(\text{Select}[f, g_{\gamma_b}]) \leq L(f) + n + 2$  then
14:        Add  $\gamma_b$  to  $PartialCandidates_{(i+1)}$ .
15:      end if
16:    end for
17:    Set  $i = i + 1$ .
18:  end while
19:  Set  $Candidates = PartialCandidates_{(N)}$ .
20:
21: Part 2: Finding an optimal pair within Candidates
22:  for all pairs  $g, h \in Candidates$  and for all gates  $\nabla \in \{\wedge, \vee\}$  do
23:    if  $L(g) + L(h) = L(f)$  and  $f = g \nabla h$  then
24:      return  $\{g, \nabla, h\}$  .
25:    end if
26:  end for
27: end procedure

```

836

837 5.1 Correctness of Algorithm 2

838 In this subsection we show that Algorithm 2 has the desired input/output behavior.

839 Fix some function f with n -inputs satisfying $L(f) \geq 2$. Let $N = 2^n$.

840 **Part 1: building *Candidates*.** First, we will prove some loop invariants that will help us
841 show that *Candidates* and $PartialCandidates_{(i)}$ contain those functions we are interested
842 in and do not contain many more things.

843 The following claim shows that the x^* described on Line 10 always exists and that
844 the ?-values of partial functions in $PartialCandidates_{(i)}$ always have an easily computable

845 structure.

846 ▷ **Claim 36.** Before and after each iteration of the while loop, it is true that if $\gamma \in$
847 $PartialCandidates_{(i)}$, then

- 848 ■ $\gamma(x) = ? \iff x \geq i$ (interpreting i as a binary string in $\{0, 1\}^n$ in the natural way),
- 849 ■ and consequently $|\gamma^{-1}(\{0, 1\})| = i$.

850 **Proof.** Clearly the claim is satisfied before the first iteration of the while loop when $i = 0$
851 and $PartialCandidates_{(i)} = \{AllUnknown\}$.

852 Now, we must argue inductively. Suppose $1 \leq i \leq N$ and $\gamma' \in PartialCandidates_{(i)}$.
853 Then, it follows that there is some $\gamma \in PartialCandidates_{(i-1)}$ and some $b \in \{0, 1\}$ such
854 that $\gamma' = \gamma_b$ where γ_b is as defined in the pseudocode. That is, γ_b is equal to γ except that
855 the first ?-value (which occurs at $x_{old}^* = i - 1$ by the inductive hypothesis) is replaced by a b .
856 Thus, we have

$$857 \quad \gamma'(x) = ? \iff \gamma(x) = ? \wedge (x \neq x_{old}^*) \iff x > x_{old}^* \iff x \geq i$$

858 where the first equivalence comes from the definition of $\gamma_b = \gamma'$ and the second equivalence
859 comes from the fact that $x_{old}^* = i - 1$. ◁

860 Next, we show that the $PartialCandidates_{(i)}$ never contains “redundant” partial functions.
861

862 ▷ **Claim 37.** Before and after each iteration of the while loop, it is true that if γ' and γ''
863 are distinct elements of $PartialCandidates_{(i)}$, then no total function agrees with both γ'
864 and γ'' .

865 **Proof.** Before the first iteration of the while loop runs, $i = 0$ and $PartialCandidates_{(0)}$ only
866 contains the single partial function $AllUnknown$, so the claim clearly holds.

867 Now we must show that the claim holds inductively. Assume $1 \leq i \leq N$. For contradiction,
868 suppose there was some total function q that agrees with distinct elements μ and μ' from
869 $PartialCandidates_{(i)}$. It follows that there exists some $b, b' \in \{0, 1\}$ and some (possibly not
870 distinct) $\gamma, \gamma' \in PartialCandidates_{(i-1)}$ such that $\mu = \gamma_b$ and $\mu' = \gamma'_{b'}$ (using the notation
871 from the pseudocode where these functions γ_b and $\gamma'_{b'}$ are given by replacing the output of
872 the first ?-valued input in γ or γ' respectively with a b -value or b' -value respectively). It
873 follows that q must also agree with γ and γ' .

874 Either $\gamma \neq \gamma'$ or not. If $\gamma \neq \gamma'$, then q agrees with two distinct elements from
875 $PartialCandidates_{(i-1)}$ which contradicts the inductive hypothesis.

876 Now suppose that $\gamma = \gamma'$. Then it must be that $b \neq b'$ (otherwise, $\mu = \mu'$ and we assumed
877 they are distinct). But then, we have then γ and γ' have the same first ?-valued input x^* , so

$$878 \quad b = \mu(x^*) = q(x^*) = \mu'(x^*) = b'$$

879 which contradicts that $b \neq b'$. ◁

880 Moreover, $PartialCandidates_{(i)}$ only contains partial functions that can be completed
881 to total functions that pass a certain test.

882 ▷ **Claim 38.** Before and after each iteration of the while loop, it is true that if $\gamma \in$
883 $PartialCandidates_{(i)}$ then there exists a function g on n -inputs that agrees with γ such that

$$884 \quad L(\text{Select}[f, g]) \leq L(f) + n + 2.$$

31:24 Connecting Perebor Conjectures

885 Proof. Before the first iteration of the while loop runs, $i = 0$ and $PartialCandidates_{(0)}$
 886 only contains one partial function ($AllUnknown$). The function f clearly agrees with
 887 $AllUnknown$, and it is easy to see that $L(Select[f, f]) = L(f) \leq L(f) + n + 1$, as desired.
 888 Thus, the claim holds before the first iteration of the while loop.

889 Moreover, the claim clearly continues holding inductively because before any γ_b is added
 900 to $PartialCandidates_{(i)}$, we check to see if the function g_{γ_b} satisfies

$$901 \quad L(Select[f, g_{\gamma_b}]) \leq L(f) + n + 2$$

902 and g_{γ_b} agrees with γ_b by construction. ◁

903 Finally, we show that $PartialCandidates_{(i)}$ always contains the partial functions we
 904 want.

905 ▷ **Claim 39.** Suppose some function q is in an optimal subcomputation for f . Then before
 906 and after each iteration of the while loop there is a $\gamma \in PartialCandidates_{(i)}$ such that q
 907 agrees with γ . Moreover, once part 1 is finished, $q \in Candidates$

908 Proof. Fix some q as in the statement of the claim.

909 Before the first iteration of the while loop runs, $i = 0$ and $PartialCandidates_{(0)}$ contains
 900 the all-? partial function $AllUnknown$, so q agrees with $AllUnknown$ and the claim holds.

901 Now, we must show the claim holds inductively. Assume $1 \leq i \leq N$. Then by induction
 902 there exists a $\gamma \in PartialCandidates_{(i-1)}$ such that q agrees with γ . Let $b = q(i-1)$. Then
 903 q agrees with γ_b as defined in the pseudocode (replacing the first ?-value in γ with a b -value)
 904 since Claim 36 implies that

$$905 \quad \gamma_b(x) = \begin{cases} b & , \text{ if } x = i - 1 \\ \gamma(x) & , \text{ otherwise.} \end{cases} .$$

906 Thus, if we could show $\gamma_b \in PartialCandidates_{(i)}$, we would be done with showing the first
 907 part of the claim. From the pseudocode, it is clear $\gamma_b \in PartialCandidates_{(i)}$ if

$$908 \quad L(Select[f, g_{\gamma_b}]) \leq L(f) + n + 2,$$

909 where g_{γ_b} is as defined in the code (the function given by replacing the ?-values in γ_b with
 910 ones) which we now prove.

911 We already noted that

$$912 \quad \gamma_b(x) = \begin{cases} b & , \text{ if } x = i - 1 \\ \gamma(x) & , \text{ otherwise.} \end{cases} .$$

913 Thus, appealing to Claim 36, we know that $\gamma_b(x) = ? \iff x > x^*$ where $x^* \in \{0, 1\}^n$ is the
 914 binary string equivalent to $i-1$ (note that $0 \leq i-1 \leq N-1$ so this makes sense). Hence, since
 915 q agrees with γ_b , we have that $g_{\gamma_b}(x) = q(x) \vee GrtrThan_{x^*}(x)$ where $GrtrThan_{x^*}(x) = 1$ if
 916 and only if $x > x^*$.

917 Thus, we have that

$$918 \quad Select[f, g_{\gamma_b}](x, z) = \begin{cases} f(x) & , \text{ if } z = 0 \\ g_{\gamma_b}(x) & , \text{ if } z = 1 \end{cases} \\ 919 \quad \quad \quad = Select[f, q](x, z) \vee (z \wedge GrtrThan_{x^*}(x)) \\ 920$$

921 Since $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$, we know that $L(\text{Select}[f, q]) = L(f) + 1$ by Lemma 24,
922 and Proposition 16 implies that $L(\text{GrtrThan}_{x^*}) \leq n$. Hence, we have that

$$923 \quad L(\text{Select}[f, g_{\gamma_b}]) \leq L(f) + n + 2.$$

924 Finally, we show that $q \in \text{Candidates}$ after part 1 finishes. Clearly, it suffices to show
925 that $q \in \text{PartialCandidates}_{(N)}$ after part 1 finishes. We have already shown that there is a
926 $\gamma \in \text{PartialCandidates}_{(N)}$ such that γ agrees with q . However, Claim 36 implies that γ is a
927 total function and hence it equals q , so $q \in \text{PartialCandidates}_{(N)}$. \triangleleft

928 **Part 2: Finding a g, h pair within Candidates .** First, we note that any output by Al-
929 gorithm 2 must be correct.

930 \triangleright **Claim 40.** Any value Algorithm 2 outputs must be an element of $\text{OptSubcomps}(f)$.

931 *Proof.* Any output $\{g, \nabla, h\}$ of Algorithm 2 must satisfy $f = g \nabla h$ and $L(f) = L(g) + L(h)$
932 which implies $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$ by Lemma 22. \triangleleft

933 Finally, we show that Algorithm 2 must output a value.

934 \triangleright **Claim 41.** Algorithm 2 must output a value (on input f).

935 *Proof.* Since $L(f) \geq 2$, we have that $\text{OptSubcomps}(f)$ is non-empty. Let $\{g, \nabla, h\} \in$
936 $\text{OptSubcomps}(f)$.

937 Claim 39 implies that $\{g, h\} \subseteq \text{Candidates}$. On the other hand, Lemma 22 implies that
938 $L(f) = L(g) + L(h)$ and $f = g \nabla h$. Thus, it is clear that part 2 will either output $\{g, \nabla, h\}$ or
939 output a value before that. \triangleleft

940 5.2 Running Time of Algorithm 2

941 Fix some function f with n -inputs satisfying $L(f) \geq 2$. Let $N = 2^n$. We break the running
942 time analysis into the two pieces of the algorithm.

943 **Part 1.** It is easy to see that the run time of part 1 can be bounded by

$$944 \quad O\left(N + \sum_{i \in [N]} N \cdot |\text{PartialCandidates}_{(i)}|\right)$$

945 where $|\text{PartialCandidates}_{(i)}|$ indicates the size of $\text{PartialCandidates}_{(i)}$ after Algorithm 2
946 is finished adding elements to it.

947 Moreover, we can bound the quantity $|\text{PartialCandidates}_{(i)}|$ as follows. Claim 38 implies
948 that every partial function in $\text{PartialCandidates}_{(i)}$ must be consistent with some total
949 function g on n -inputs satisfying

$$950 \quad L(\text{Select}[f, g]) \leq L(f) + n + 2.$$

951 On the other hand, Claim 37 implies that any single (total) function can agree with at most
952 one partial function in $\text{PartialCandidates}_{(i)}$. Hence, we have that

$$953 \quad |\text{PartialCandidates}_{(i)}| \leq |\{g : L(\text{Select}[f, g]) \leq L(f) + n + 2\}|$$

954 and Lemma 25 implies that

$$955 \quad |\{g : L(\text{Select}[f, g]) \leq L(f) + n + 2\}| \leq O(|\text{CanonOpt}_{n+1} \text{Formulas}(f)| \cdot N^2 \log N).$$

956 Thus, we have that part 1 runs in time at most $O(|\text{CanonOpt}_{n+1} \text{Formulas}(f)| \cdot N^4 \log N)$.
957 Moreover, part 1 only makes oracle calls of length at most $2N$ (to calculate $L(\text{Select}[f, g_{\gamma_b}])$).

31:26 Connecting Perebor Conjectures

958 **Part 2.** It is easy to see that this part runs in time $O(N \cdot |Candidates|^2)$. Hence, since
959 $Candidates = PartialCandidates_{(N)}$, the analysis in part 1 above implies that

$$960 \quad |Candidates| \leq O(|CanonOpt_{n+1}Formulas(f)| \cdot N^2 \log N).$$

961 Thus, part 2 runs in time at most

$$962 \quad O(|CanonOpt_{n+1}Formulas(f)|^2 \cdot N^5 \log^2 N).$$

963 Moreover, part 2 only makes oracle calls of length N .

964 **In total.** Putting it all together, we have that Algorithm 2 runs in time at most

$$965 \quad O(|CanonOpt_{n+1}Formulas(f)|^2 \cdot N^5 \log^2 N)$$

966 and only makes oracle queries of length $2N$. ◀

967 **6 A worst-case randomized reduction**

968 We now present a worst-case search to decision reduction for MFSP.

969 ▶ **Theorem 42.** *There is a randomized algorithm solving Search-MFSP on inputs of length*
970 *N in time $O(2^{.67N})$ given access to an oracle that solves MFSP on instances of length at*
971 *most $2N$.*

972 **Proof.** We prove this theorem by giving an oracle algorithm solving `DecompProblem` and
973 appealing to Theorem 21. We provide the pseudocode of our algorithm in Algorithm 3, which
974 we recommend the reader look at before proceeding.

975 **6.1 Correctness of Algorithm 3**

976 In this subsection, we prove that Algorithm 3 has the desired input/output behavior. In our
977 analysis, we will use s and t as parameters which we will set to the optimal values (which
978 are written in the pseudocode) in Section 6.2 where we do the running time analysis for
979 Algorithm 3.

980 Fix some function f on n -inputs with $L(f) \geq 2$. We analyze the algorithm in parts.

981 **Part 1.** Since φ_i is chosen to have $L(f)$ leaves and the algorithm in part 1 checks if φ_i
982 computes f before returning any value, the following claim is clear.

983 ▷ **Claim 43.** Any output by Algorithm 3 returned in part 1 must be an element of
984 $OptSubcomps(f)$.

985 Moreover, we can lower bound the probability that Algorithm 3 returns a value in part 1
986 as follows. Recall that $CanonOpt_0Formulas(f)$ is the set of optimal canonical formulas for f .
987 We will show that part 1 succeeds if this set is large.

988 ▷ **Claim 44.** If $t \geq 5 \cdot \frac{2^{N(1+o(1))}}{|CanonOpt_0Formulas(f)|}$, then part 1 of Algorithm 3 will return a value at
989 least 99% of time.

■ **Algorithm 3** A randomized worst-case search to decision reduction for MFSP

```

1: procedure WORSTCASEOPTIMALSUBCOMPUTATION( $f$ )
  ▷ Given the length- $N$  truth table of a function  $f$  that takes  $n$ -inputs with  $L(f) \geq 2$ , this
  procedure returns an element  $\{g, \nabla, h\}$  of  $\text{OptSubcomps}(f)$ .

2:   Set  $s = \frac{2}{3} \cdot \frac{2^n}{\log n}$ 
3:   Set  $t = 2^{2N/3}$ 
4:
5: Part 1: Try random formulas
6:   for  $i = 1, \dots, t$  do
7:     Let  $G_i$  be a uniformly random binary tree with  $L(f)$ -leaves. (Section 6.2 discusses
  how to sample  $G_i$ .)
8:     Turn  $G_i$  into a uniformly random formula  $\varphi_i$  by picking uniformly random gates
  from  $\{\wedge, \vee\}$  and uniformly random input leaves from  $\{0, 1, x_1, \dots, x_n, \neg x_1, \dots, \neg x_n\}$ .
9:     if  $\varphi_i$  computes  $f$  then
10:      Write  $\varphi_i = \varphi_{i,1} \nabla \varphi_{i,2}$ .
11:      Let  $g$  and  $h$  be the function computed by  $\varphi_{i,1}$  and  $\varphi_{i,2}$  respectively.
12:      if  $L(f) = L(g) + L(h)$  then
13:        return  $\{g, \nabla, h\}$ .
14:      end if
15:    end if
16:  end for
17:
18: Part 2: Generate a small list of candidates for  $g$ 
19:   Set  $\text{SmallFuncs} = \{g : g \text{ is a Boolean function with } n\text{-inputs and } L(g) \leq s\}$ .
20:   Set  $\text{Candidates} = \{g \in \text{SmallFuncs} : L(\text{Select}[f, g]) \leq L(f) + 1\}$ .
21:
22: Part 3: Try to find a  $g, h$  pair within Candidates
23:   for each pair of functions  $g, h \in \text{Candidates}$  and for each gate  $\nabla \in \{\wedge, \vee\}$  do
24:     if  $f = g \nabla h$  and  $L(f) = L(g) + L(h)$  then
25:       return  $\{g, \nabla, h\}$ .
26:     end if
27:   end for
28:
29: Part 4: Try to find a  $g, h$  pair by looking at functions  $h$  satisfying  $f = g \nabla h$ 
30:   Set  $\text{SmallCandidates} = \{g \in \text{Candidates} : L(g) \leq L(f) - s\}$ .
31:   for each function  $g \in \text{SmallCandidates}$  and for each  $\nabla \in \{\wedge, \vee\}$  do
32:     if  $\forall x \in \{0, 1\}^n \exists b \in \{0, 1\}$  such that  $g(x) \nabla b = f(x)$  then
33:       Let  $h_{?,g} : \{0, 1\}^n \rightarrow \{0, 1, ?\}$  be the unique partial function on  $n$ -inputs such
  that  $\forall h, f = g \nabla h \iff h$  agrees with  $h_{?,g}$ .
34:       for each total function  $h$  that agrees with  $h_{?,g}$  do
35:         if  $f = g \nabla h$  and  $L(f) = L(g) + L(h)$  then
36:           return  $\{g, \nabla, h\}$ .
37:         end if
38:       end for
39:     end if
40:   end for
41: end procedure

```

31:28 Connecting Perebor Conjectures

990 Proof. Since we are picking each $L(f)$ -leaf formula φ_i uniformly at random, the probability
 991 that any fixed formula computes f is at least

$$992 \quad \frac{|\text{CanonOpt}_0\text{Formulas}(f)|}{\text{the total number of formulas with } L(f) \text{ leaves}}$$

993 Combining Theorem 14 with Proposition 13 upper bounds the denominator by $2^{N(1+o(1))}$, so

$$994 \quad \Pr[\varphi_i \text{ computes } f] \geq \frac{|\text{CanonOpt}_0\text{Formulas}(f)|}{2^{N(1+o(1))}}.$$

995 Since each of these φ_i are chosen independently, we have that

$$\begin{aligned} 996 \quad \Pr[\exists i \in [t] \text{ such that } \varphi_i \text{ computes } f] &\geq 1 - \left(1 - \frac{|\text{CanonOpt}_0\text{Formulas}(f)|}{2^{N(1+o(1))}}\right)^t \\ 997 &\geq 1 - e^{-t \cdot \frac{|\text{CanonOpt}_0\text{Formulas}(f)|}{2^{N(1+o(1))}}} \\ 998 &\geq 1 - e^{-5} \\ 999 &\geq .99 \\ 1000 \end{aligned}$$

1001 Hence, with probability at least 99%, part 1 will find a φ_i computing f at which point it
 1002 will clearly return a value. \triangleleft

1003 **Part 2.** In part 2, Algorithm 3 constructs the *Candidates* set. We prove two claims about
 1004 this set. First, that it contains the functions we care about, and second that its size can be
 1005 bounded using the size of the $\text{CanonOpt}_0\text{Formulas}(f)$ set.

1006 \triangleright **Claim 45.** Suppose g is in an optimal subcomputation for f . Then $L(g) \leq s \implies g \in$
 1007 *Candidates*.

1008 Proof. Since $L(g) \leq s$, we know that $g \in \text{SmallFuncs}$. Next, since g is in an optimal
 1009 subcomputation for f , we have by Lemma 24 that

$$1010 \quad L(\text{Select}[f, g]) \leq L(f) + 1,$$

1011 so g is an element of *Candidates*. \triangleleft

\triangleright **Claim 46.**

$$1012 \quad |\text{Candidates}| = O(|\text{CanonOpt}_0\text{Formulas}(f)| \cdot N \log N)$$

1013 Proof. By construction, we have that

$$1014 \quad \text{Candidates} \subseteq \{g : L(\text{Select}[f, g]) = L(f) + 1\}.$$

1015 On the other hand, Lemma 25, we have that

$$1016 \quad |\{g : L(\text{Select}[f, g]) = L(f) + 1\}| \leq O(|\text{CanonOpt}_0\text{Formulas}(f)| \cdot N \log N)$$

1017 \triangleleft

1018 **Part 3.** In Part 3, Algorithm 3 tries to find a g, h pair by looking within the *Candidates*
 1019 set. We show this works as long as there is a $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$ where $L(g)$ and
 1020 $L(h)$ are at most s .

1021 First, we note that part 3 can only return correct answers.

1022 \triangleright **Claim 47.** Any output returned by Algorithm 3 in part 3 will be an element of
 1023 $\text{OptSubcomps}(f)$.

1024 *Proof.* In order for a $\{g, \nabla, h\}$ value to be returned in part 3 it must satisfy $f = g \nabla h$ and
 1025 $L(f) = L(g) + L(h)$. Thus, by Lemma 22, we know $\{g, \nabla, h\} \in \text{OptSubcomps}(f)$. \triangleleft

1026 Next, we give sufficient conditions on which part 3 will return an answer.

1027 \triangleright **Claim 48.** If there exists an element $\{g', \nabla, h'\}$ of $\text{OptSubcomps}(f)$ such that

$$1028 \quad \max\{L(g'), L(h')\} \leq s,$$

1029 then Algorithm 3 will return a value in part 3 or before.

1030 *Proof.* Suppose there exists an element $\{g', \nabla, h'\}$ of $\text{OptSubcomps}(f)$ such that

$$1031 \quad \max\{L(g'), L(h')\} \leq s,$$

1032 and assume that this procedure has not returned a value before it reaches part 3. Then
 1033 by Claim 45, we have that both g' and h' are in *Candidates*. Moreover, since $\{g', \nabla, h'\} \in$
 1034 $\text{OptSubcomps}(f)$, we know that $f = g' \nabla h'$ and $L(f) = L(g') + L(h')$ by Lemma 22. Hence
 1035 the for loop will return an output if it reaches the values $g = g', h = h'$, and $\nabla = \nabla'$, or the
 1036 algorithm will return an output before reaching these values. \triangleleft

1037 **Part 4.** In the final part of Algorithm 3, we look for matching h functions for g candidates
 1038 with small complexity.

1039 First, we note that any output returned by part 4 must be correct by essentially the same
 1040 proof as Claim 47 in part 3.

1041 \triangleright **Claim 49.** Any output returned by Algorithm 3 in part 4 will be an element of
 1042 $\text{OptSubcomps}(f)$.

1043 Next, we show sufficient conditions for part 4 returning an answer.

1044 \triangleright **Claim 50.** If $s \geq L(f)/2$ and there exists a $\{g', \nabla, h'\} \in \text{OptSubcomps}(f)$ such that
 1045 $L(h') \geq s$, then Algorithm 3 will return a value in part 4 or earlier.

1046 *Proof.* Using Lemma 22, we have $L(f) = L(g') + L(h')$. Thus, since $s \geq L(f)/2$ and $L(h') \geq s$,
 1047 we have that

$$1048 \quad L(g') = L(f) - L(h') \leq L(f) - s \leq 2s - s = s.$$

1049 Hence, by Claim 45, we have that $g' \in \text{Candidates}$. Moreover, since $L(g') \leq L(f) - s$, it
 1050 follows that $g' \in \text{SmallCandidates}$. Thus, it is clear that part 4 will return a value if its for
 1051 loop ever reaches $g = g', \nabla = \nabla'$, and $h = h'$ (though it could return a value before that).
 1052 \triangleleft

31:30 Connecting Perebor Conjectures

1053 **In total.** Finally, we can prove the correctness of the input/output behavior of Algorithm 3.
1054

1055 \triangleright **Claim 51.** If $s \geq L(f)/2$, then Algorithm 3 (run on input f) returns an element of
1056 $\text{OptSubcomps}(f)$.

1057 **Proof.** Put together, Claim 43, Claim 47, and Claim 49 ensures that any output returned by
1058 Algorithm 3 must be an element of $\text{OptSubcomps}(f)$.

1059 Hence, it suffices to show that Algorithm 3 will always output a value. We divide
1060 into two cases. Either there exists an element $\{g', \nabla, h'\} \in \text{OptSubcomps}(f)$ such that
1061 $\max\{L(g'), L(h')\} \leq s$ or not.

1062 If there exists such an element, then Claim 48 ensures that Algorithm 3 will output a
1063 value.

1064 Now suppose that for all $\{g', \nabla, h'\} \in \text{OptSubcomps}(f)$ we have $\max\{L(g'), L(h')\} \geq s$.
1065 Since $L(f) \geq 2$, we know $\text{OptSubcomps}(f)$ is non-empty by Proposition 19. Hence we can
1066 fix some $\{g', \nabla, h'\} \in \text{OptSubcomps}(f)$ satisfying $\max\{L(g'), L(h')\} \geq s$. Without loss of
1067 generality we can assume that $L(g') \leq L(h')$. Thus, we have that $L(h') \geq s$, and by hypothesis
1068 $s \geq L(f)/2$, so Claim 50 ensures Algorithm 3 outputs a value. \triangleleft

1069 Thus Algorithm 3 is correct as long as $s \geq L(f)/2$. Indeed, in the next section we will set
1070 s so that $s \geq \max\{L(f)/2 : f \text{ takes } n\text{-inputs}\}$.

1071 6.2 Runtime of Algorithm 3

1072 In this subsection, we bound the runtime of Algorithm 3 and set s and t to the optimal
1073 values. We analyze Algorithm 3 in its parts.

1074 **Part 1.** The for loop in part 1 clearly runs t times, so we just need to bound the running
1075 time of each iteration. Generating a uniformly random binary with $L(f)$ -leaves can be done in
1076 linear time (see [15] for a survey of various approaches). The other operations in the for loop
1077 can clearly be done in time $O(N + L(f))$. Hence, all of part 1 runs in time $O(t \cdot (N + L(f)))$
1078 which is $O(t \cdot N)$ using the worst-case formula upper bound from Theorem 14.

1079 Moreover, part 1 only makes oracle calls of length N (to calculate $L(f)$).

1080 **Part 2.** Building the *SmallFuncs* set requires iterating through all formulas of size s
1081 (which is bounded by $2^{(1+o(1)) \cdot s \log n}$ using Proposition 13) and then computing the truth
1082 table of each of these size s formulas (which can be done in time $O(Ns)$). Hence, computing
1083 *SmallFuncs* can be done in $O(N \cdot 2^{(1+o(1)) \cdot s \log n})$ time. Moreover, $|\text{SmallFuncs}|$ is clearly
1084 upper bounded by the upper bound on the number of formulas of size s : $2^{(1+o(1)) \cdot s \log n}$.

1085 Next, building the *Candidates* set can be done in time $O(|\text{SmallFuncs}| + N) = O(N \cdot$
1086 $2^{(1+o(1)) \cdot s \log n})$, and we use oracle calls of length $2N$ in this step (for $\text{Select}[f, g]$).

1087 Hence, part 2 runs in time $O(N \cdot 2^{(1+o(1)) \cdot s \log n})$.

1088 We will make use of the following claim later, which bounds the size of the *Candidates*
1089 set if part 1 did not return a value.

1090 \triangleright **Claim 52.** Fix some function f . Then with 99% probability (over the algorithm's choice
1091 of random formulas) either Algorithm 3 on input f returns before reaching part two or

$$1092 \quad |\text{Candidates}| \leq \frac{2^{N(1+o(1))}}{t}.$$

1093 Proof. Let $\alpha(\cdot) = o(1)$ be the function guaranteed to exist by Claim 44 such that if

$$1094 \quad |\text{CanonOpt}_0\text{Formulas}(f)| \geq 5 \frac{2^{N(1+\alpha(N))}}{t}$$

1095 then Algorithm 3 will return in part 1 with 99% probability. Let $\beta(\cdot) = o(1)$ be some function
1096 we will specify later.

1097 Suppose that *Algorithm 3* reaches part two on input f and

$$1098 \quad |\text{Candidates}| > \frac{2^{N(1+\beta(N))}}{t}.$$

1099 Then Claim 46 implies that

$$1100 \quad \frac{2^{N(1+\beta(N))}}{t} \leq O(|\text{CanonOpt}_0\text{Formulas}(f)|N \log n).$$

1101 Thus, by choosing $\beta(\cdot)$ to be large enough relative to $\alpha(\cdot)$, we can conclude that

$$1102 \quad |\text{CanonOpt}_0\text{Formulas}(f)| \geq 5 \frac{2^{N(1+\alpha(N))}}{t},$$

1103 so Algorithm 3 will return in part 1 with 99% probability. \triangleleft

1104 **Part 3.** It is easy to see that part 3 runs in time $O(|\text{Candidates}|^2 + N)$ and makes oracle
1105 calls of length N .

1106 Thus, using Claim 52, we have that with 99% probability part 3 runs in time $\frac{2^{2N(1+o(1))}}{t^2}$.

1107 **Part 4.** Computing *SmallCandidates* can be done in $O(|\text{Candidates}| + N)$ time, and the
1108 outer for loop runs at most $O(|\text{Candidates}|)$ many times.

1109 It remains to bound the running time of each iteration of the outer for loop. The if
1110 condition can be checked in $O(N)$ time. Constructing $h_{\gamma,g}$ also takes $O(N)$ time (similar to
1111 the if condition, just iterate through each input $x \in \{0,1\}^n$ and see which values of $b \in \{0,1\}$
1112 satisfy $f(x) = g(x) \nabla b$). Each iteration of the inner for loop takes $O(N)$ time. Finally, the
1113 inner for loop runs $2^{|h_{\gamma,g}^{-1}(?)|}$ many times.

1114 Thus, the total running time for part 4 is

$$1115 \quad O(|\text{Candidates}| \cdot (N + N \cdot \max\{2^{|h_{\gamma,g}^{-1}(?)|} : g \in \text{SmallCandidates}\}))$$

1116 time. Moreover, we can bound the quantity $|h_{\gamma,g}^{-1}(?)|$ when $g \in \text{SmallCandidates}$ as follows.

1117 \triangleright Claim 53. If $g \in \text{SmallCandidates}$, then

$$1118 \quad |h_{\gamma,g}^{-1}(?)| \leq (1 + o(1))(N - s \log n).$$

1119 Proof. Since any function h that agrees with $h_{\gamma,g}$ satisfies $g \nabla h = f$ and, we have that

$$1120 \quad \mathsf{L}(f) \leq \mathsf{L}(g) + \mathsf{L}(h_{\gamma,g}).$$

1121 On the other hand, since $g \in \text{SmallCandidates}$, $\mathsf{L}(g) \leq \mathsf{L}(f) - s$. Combining these two
1122 inequalities, we get

$$1123 \quad \mathsf{L}(h_{\gamma,g}) \geq s.$$

31:32 Connecting Peregbor Conjectures

1124 But the upper bound on the formula complexity of partial functions from Theorem 17
1125 implies that

$$1126 \quad \mathsf{L}(h_{?,g}) \leq (1 + o(1)) \left(1 - \frac{|h_{?,g}^{-1}(?)|}{N}\right) \frac{N}{\log n}.$$

1127 Hence

$$1128 \quad s \leq (1 + o(1)) \left(1 - \frac{|h_{?,g}^{-1}(?)|}{N}\right) \frac{N}{\log n}$$

1129 so

$$1130 \quad |h_{?,g}^{-1}(?)| \leq N - \frac{s \log n}{(1 + o(1))} \leq (1 + o(1))(N - s \log n).$$

1131

◁

1132 Thus, using Claim 52, we have that with 99% probability part 4 runs in

$$1133 \quad O\left(\frac{2^{N(1+o(1))}}{t} \cdot N \cdot 2^{(1+o(1))(N-s \log n)}\right) = \frac{2^{(1+o(1))(2N-s \log n)}}{t}$$

1134 time.

1135 **In total.** Thus, we get that with 99% probability Algorithm 3 runs in time

$$1136 \quad O(t \cdot N) + O(N \cdot 2^{(1+o(1)) \cdot s \log n}) + \frac{2^{2N(1+o(1))}}{t^2} + \frac{2^{(1+o(1))(2N-s \log n)}}{t}.$$

1137 Letting $s = \frac{2}{3} \frac{2^n}{\log n}$ and $t = 2^{\frac{2}{3}N}$, we get that the running time is bounded by

$$1138 \quad 2^{(1+o(1))\frac{2}{3}N}.$$

1139 Moreover, s will satisfy $s \geq \mathsf{L}(f)/2$ (as required for the correctness of the algorithm) for
1140 all f with n -inputs when n is sufficiently large by Theorem 14.

1141

◀

1142 **7 A “bottom-up” reduction for DeMorgan Formulas**

1143 In this section, we provide another algorithm for solving Search-MFSP that is also efficient
1144 on average, though with worse guarantees than the one given by Theorem 34. Despite its
1145 worse guarantees, we present the algorithm because it uses a different “bottom-up” approach
1146 that we think is interesting.

1147 We begin by proving a lemma that bounds the depth of optimal DeMorgan formulas.

1148 ► **Lemma 54** (Large optimal DeMorgan formulas have not too large depth). *Let $f : \{0, 1\}^n \rightarrow$
1149 $\{0, 1\}$. Let φ be an optimal DeMorgan formula for computing f . Then the depth of f is at
1150 most $\frac{10}{n} \cdot 2^n$ for sufficiently large n .*

1151 **Proof.** Let d be a parameter we set later. For contradiction, suppose that φ is an optimal
1152 formula for computing f with depth greater than d . Clearly then $\mathsf{L}(f) > d$ as well. For φ
1153 to have depth greater than d , there must be gates $\nabla_1, \dots, \nabla_{d-1} \in \{\wedge, \vee\}$ and subformulas
1154 $\varphi_1, \dots, \varphi_d$ such that

$$1155 \quad \varphi = \varphi_1 \nabla_1 \varphi_2 \nabla_2 \dots \nabla_{d-1} \varphi_d$$

1156 where we evaluate gates from left to right, so this formula with parentheses would be

$$1157 \quad (\dots((\varphi_1 \nabla_1 \varphi_2) \nabla_2 \varphi_3) \dots) \nabla_{d-1} \varphi_d,$$

1158 and $|\varphi_i| \geq 1$ for all $i \in [d]$. In other words, consider a d -length path from some subformula
1159 φ_1 to the output gate ∇_{d-1} in the formula and let $\varphi_2, \dots, \varphi_d$ be all the subformulas in φ
1160 from bottom to top (viewing the output gate as the top) intersecting this path. Similarly, let
1161 $\nabla_1, \dots, \nabla_{d-1}$ be the gates in order from bottom to top along this path.

1162 Then, we have that

$$1163 \quad \mathsf{L}(f) = |\varphi| = \sum_{i \in [d]} |\varphi_i|.$$

1164 Thus, we have that

$$1165 \quad \mathbb{E}_{i \in [d] \setminus \{1\}} [|\varphi_i|] \leq \frac{\mathsf{L}(f) - 1}{d - 1}.$$

1166 Hence by Markov's inequality, we have that there exists a subset $S \subseteq [d] \setminus \{1\}$ of size at
1167 least $\frac{d-1}{2}$ such that for all $i \in S$ we have $|\varphi_i| \leq 2 \cdot \frac{\mathsf{L}(f)-1}{d-1}$.

1168 On the other hand the number of distinct formulas on n -inputs with size at most $2 \cdot \frac{\mathsf{L}(f)-1}{d-1}$
1169 is bounded by

$$1170 \quad 2^{2 \cdot \frac{\mathsf{L}(f)-1}{d-1} \log n(1+o(1))}$$

1171 according to Proposition 13. Assume that we have chosen d so that

$$1172 \quad |S| \geq \frac{d-1}{2} > 2^{\frac{\mathsf{L}(f)-1}{d-1} \log n(1+o(1))}.$$

1173 Then, by the pigeonhole principle, there exists $i < j \in S$ such that φ_i and φ_j compute the
1174 same function. We can use this to get a contradiction to optimality as follows. Assume that
1175 $\nabla_{i-1} = \nabla_{j-1} = \wedge$ (the other cases are similar). Then, substituting in $\nabla_{i-1} = \nabla_{j-1} = \wedge$ we
1176 would have that the subformula of φ computed at ∇_{i-1} , that is

$$1177 \quad \varphi_1 \nabla_1 \varphi_2 \nabla_2 \dots \nabla_{j-2} \varphi_{j-1} \nabla_{j-1} \varphi_j \nabla_j \dots \nabla_{i-1} \varphi_i,$$

1178 equals the function computed by

$$1179 \quad \varphi_1 \nabla_1 \varphi_2 \nabla_2 \dots \nabla_{j-2} \varphi_{j-1} \wedge \varphi_j \nabla_j \dots \wedge \varphi_i$$

1180 However if $\varphi_i(x) = 0$, then intuitively this formula outputs 0 no matter what happens on
1181 the to the "left" of φ_i in the formula. Thus, we might as well assume on the "left" that
1182 $\varphi_i(x) = \varphi_j(x) = 1$. Thus we get that the function computed at gate ∇_{i-1} is also computed
1183 by the following simplified formula:

$$1184 \quad \varphi_1 \nabla_1 \varphi_2 \nabla_2 \dots \nabla_{j-2} \varphi_{j-1} \wedge 1 \nabla_j \dots \wedge \varphi_i.$$

1185 which equals

$$1186 \quad \varphi_1 \nabla_1 \varphi_2 \nabla_2 \dots \nabla_{j-2} \varphi_{j-1} \nabla_j \dots \wedge \varphi_i.$$

1187 Thus, while the original subformula of φ computed at gate ∇_{i-1} given by

$$1188 \quad \varphi_1 \nabla_1 \varphi_2 \nabla_2 \dots \varphi_{j-1} \nabla_{j-1} \varphi_j \dots \nabla_{i-1} \varphi_i$$

31:34 Connecting Perebor Conjectures

1189 had size $\sum_{k \in [i]} |\varphi_k|$, the new equivalent formula given by

$$1190 \quad \varphi_1 \nabla_1 \varphi_2 \nabla_2 \dots \varphi_{j-1} \nabla_{j-1} \varphi_{j+1} \dots \wedge \varphi_i$$

1191 has the smaller size $\sum_{k \in [i]} |\varphi_k| - |\varphi_j| < \sum_{k \in [i]} |\varphi_k|$ which contradicts the optimality of φ
1192 for f .

1193 It remains to chose a value for d . We need to satisfy that

$$1194 \quad \frac{d-1}{2} > 2^{2 \cdot \frac{L(f)-1}{d-1} \log n(1+o(1))}.$$

1195 By Theorem 14, we have that $L(f) \leq (1+o(1)) \frac{2^n}{\log n}$. So setting $d = \frac{10}{n} \cdot 2^n$, we get that

$$1196 \quad 2^{2 \cdot \frac{L(f)-1}{d-1} \log n(1+o(1))} \leq 2^{2n(1/10+o(1))} \leq d = \frac{10}{n} \cdot 2^n$$

1197 when n is sufficiently large. ◀

1198 Using this lemma, we prove a “bottom-up” search to decision reduction for Search-MFSP.

1199 **► Theorem 55.** *There is a deterministic “bottom-up” algorithm solving Search-MFSP on*
1200 *inputs of length N given access to an oracle that solves MFSP on instances of length $2N$ that*
1201 *runs in time $O(N^3 \cdot |\text{CanonOpt}_{(\frac{10}{n}, 2^n)} \text{Formulas}(f)|^2)$ where f is the input truth table of length*
1202 *N .*

■ **Algorithm 4** A bottom up search to decision reduction

```

1: procedure OPTIMALFORMULA( $f$ )
  ▷ Given the length- $N$  truth table of a function  $f$  that takes  $n$ -inputs, this procedure
  finds an optimal formula computing  $f$ 
2:   Set  $Candidates_{(1)} = \emptyset$ .
3:   Let  $OptForm$  be a empty lookup table.
4:   for each size one formula  $\varphi$  on  $n$ -inputs do
5:     Let  $q$  be the function computed by  $\varphi$ .
6:     Add  $q$  to  $Candidates_{(1)}$ .
7:     Let  $OptForm(q) = \varphi$ .
8:   end for
9:   Set  $s = 1$ .
10:  while  $s < L(f)$  do
11:    Set  $Candidates_{(s+1)} \leftarrow \emptyset$ .
12:    for every pair  $g, h$  in  $Candidates_{(s)}$  and every gate  $\nabla \in \{\wedge, \vee\}$  do
13:      Let  $q$  be the function computed by  $g \nabla h$ .
14:      if  $L(q) = L(g) + L(h)$  and  $L(\text{Select}[f, q]) \leq L(f) + \frac{10}{n} \cdot 2^n$  then
15:        Add  $q$  to  $Candidates_{(s+1)}$ .
16:        Set  $OptForm(q)$  to the formula given by  $OptForm(g) \nabla OptForm(h)$ .
17:      end if
18:    end for
19:    Set  $s = s + 1$ .
20:  end while
21:  return  $OptForm(f)$ .
22: end procedure

```

1203 **Proof.** The pseudocode for our reduction is presented in Algorithm 4.

1204 Since the guarantees of this algorithm are weaker than the one presented in Theorem 34,
1205 and since its proof of correctness is relatively straightforward (the intuition is given in
1206 Section 1.3) modulo one important detail, we only prove this one important detail: that the
1207 “test” used in Algorithm 4

$$1208 \quad L(\text{Select}[f, q]) - L(f) \leq d \leq \frac{10}{n} \cdot 2^n$$

1209 is passed by any function q that is computed by some gate in an optimal formula for f . Note
1210 that the bound on the total number of functions that pass this test given by Lemma 25 then
1211 yields the desired efficiency guarantees of this algorithm.

1212 Fix a function f on n -inputs and set $N = 2^n$. The correctness of this algorithm follows
1213 from showing that if φ is an optimal formula for f and q is an n -input function computed by
1214 the i th gate node in φ , then

$$1215 \quad L(\text{Select}[f, q]) - L(f) \leq d$$

1216 where d is the depth of φ . If there were the case, then

$$1217 \quad L(\text{Select}[f, q]) - L(f) \leq \frac{10}{n} \cdot 2^n$$

1218 using the depth bound on optimal DeMorgan formulas from Lemma 54.

1219 We now show that

$$1220 \quad L(\text{Select}[f, q]) - L(f) \leq d$$

1221 by producing a formula φ' for $L(\text{Select}[f, q])$ of size at most $L(f) + d$.

1222 Before we give our formal construction of φ' , we give an example of what our construction
1223 does that will hopefully be enough to convince the reader. To give an example, if $\varphi =$
1224 $x_1 \vee x_2 \wedge x_3$ (associating from left to right) and x_1 computes q , then $\varphi' = x_1 \vee (x_2 \wedge \neg z) \wedge (x_3 \vee z)$.

1225 We formally construct φ' as follows. Recall we assumed that φ has depth d that q is the
1226 function computed by the i th gate in φ . Then, we can write

$$1227 \quad \varphi = \varphi_i \nabla_{i+1} \varphi_{i+1} \nabla_{i+2} \dots \nabla_k \varphi_k$$

1228 (associating from left to right) where $k \leq d$ and $\varphi_i, \dots, \varphi_{k+1}$ are subformulas of φ and
1229 $\nabla_i, \dots, \nabla_k$ are the gates connecting those subformulas in φ and φ_i computes q .

1230 We can then construct φ' by replacing each φ_j in φ for $i + 1 \leq j \leq k$ with a new formula
1231 φ'_j given by

$$1232 \quad \varphi'_j = \begin{cases} \varphi_j \wedge \neg z, & \text{if } \nabla_j = \vee \\ \varphi_j \vee z, & \text{if } \nabla_j = \wedge \end{cases}.$$

1233 Then

$$1234 \quad \varphi' = \varphi_i \nabla_{i+1} \varphi'_{i+1} \nabla_{i+2} \dots \nabla_k \varphi'_k$$

1235 computes $\text{Select}[f, q]$ because these φ'_j are chosen so that ∇_j will always just output its other
1236 input when $z = 1$.

1237 Hence,

$$1238 \quad L(\text{Select}[f, q]) - L(f) \leq d$$

1239

1240 — **References** —

- 1241 **1** Eric Allender. The new complexity landscape around circuit minimization. In *Language and*
1242 *Automata Theory and Applications - 14th International Conference, LATA 2020, Milan, Italy,*
1243 *March 4-6, 2020, Proceedings*, volume 12038 of *Lecture Notes in Computer Science*, pages
1244 3–16. Springer, 2020.
- 1245 **2** Eric Allender, Harry Buhrman, Michal Koucký, Dieter van Melkebeek, and Detlef Ronneburger.
1246 Power from random strings. *SIAM J. Comput.*, 35(6):1467–1493, 2006.
- 1247 **3** Eric Allender and Bireswar Das. Zero knowledge and circuit minimization. *Inf. Comput.*,
1248 256:2–8, 2017.
- 1249 **4** Eric Allender, Michal Koucký, Detlef Ronneburger, and Sambuddha Roy. The pervasive reach
1250 of resource-bounded kolmogorov complexity in computational complexity theory. *Journal of*
1251 *Computer and System Sciences*, 77(1):14 – 40, 2011.
- 1252 **5** David Buchfuhrer and Christopher Umans. The complexity of boolean formula minimization.
1253 *J. Comput. Syst. Sci.*, 77(1):142–153, 2011.
- 1254 **6** Marco L. Carmosino, Russell Impagliazzo, Valentine Kabanets, and Antonina Kolokolova.
1255 Learning algorithms from natural proofs. In *Proceedings of the 31st Conference on Computa-*
1256 *tional Complexity*, 2016.
- 1257 **7** Alexander Golovnev, Rahul Ilango, Russell Impagliazzo, Valentine Kabanets, Antonina Koloko-
1258 *lova*, and Avishay Tal. $Ac^0[p]$ lower bounds against MCSP via the coin problem. In *ICALP*,
1259 volume 132 of *LIPICS*, pages 66:1–66:15, 2019.
- 1260 **8** Shuichi Hirahara. Non-black-box worst-case to average-case reductions within NP. In *59th*
1261 *IEEE Annual Symposium on Foundations of Computer Science, FOCS*, pages 247–258, 2018.
- 1262 **9** Shuichi Hirahara, Igor Carboni Oliveira, and Rahul Santhanam. NP-hardness of minimum
1263 circuit size problem for OR-AND-MOD circuits. In *33rd Computational Complexity Conference,*
1264 *CCC*, volume 102, pages 5:1–5:31, 2018.
- 1265 **10** Valentine Kabanets and Jin-Yi Cai. Circuit minimization problem. In *Proceedings of the*
1266 *Thirty-Second Annual ACM Symposium on Theory of Computing, STOC '00*, page 73–79,
1267 2000.
- 1268 **11** S. A. Lozhkin. Tighter bounds on the complexity of control systems from some classes. *Mat.*
1269 *Voprosy Kibernetiki* 6, pages 189–214 (in Russian), 1996.
- 1270 **12** Oleg B. Lupanov. Complexity of formula realization of functions of logical algebra. *Problemy*
1271 *Kibernetiki*, 3:61–80, 1960.
- 1272 **13** William J. Masek. Some NP-complete set covering problems. Unpublished Manuscript, 1979.
- 1273 **14** Cody D. Murray and R. Ryan Williams. On the (non) np-hardness of computing circuit
1274 complexity. *Theory of Computing*, 13(1):1–22, 2017.
- 1275 **15** Erkki Mäkinen. Generating random binary trees — a survey. *Information Sciences*, 115(1):123
1276 – 136, 1999.
- 1277 **16** Nicholas Pippenger. Information theory and the complexity of boolean functions. *Mathematical*
1278 *Systems Theory*, 10:129–167, 01 1977.
- 1279 **17** Alexander A. Razborov and Steven Rudich. Natural proofs. *J. Comput. Syst. Sci.*, 55(1):24–35,
1280 1997.
- 1281 **18** Michael Rudow. Discrete logarithm and minimum circuit size. *Inf. Process. Lett.*, 128:1–4,
1282 2017.
- 1283 **19** Rahul Santhanam. Pseudorandomness and the minimum circuit size problem. In *11th*
1284 *Innovations in Theoretical Computer Science Conference, ITCS*, volume 151 of *LIPICs*, pages
1285 68:1–68:26, 2020.
- 1286 **20** B. A. Trakhtenbrot. A survey of russian approaches to perebor (brute-force searches) algorithms.
1287 *IEEE Ann. Hist. Comput.*, 6(4):384–400, October 1984.